

Date of Sample Receipt: 10/15/12
Date of Sample Test: 10/16/12-10/23/12

Attenuation measurements have been performed according to the American National Standards Institute (ANSI) Specifications, ANSI S3.19-1974, using the experimenter-fit protocol, on the Detectamet Metal Detectable Polyurethane Foam Ear Plug insert-type hearing protector (test ID Q2736A). The specified threshold measurement data were obtained using ten normal-hearing listeners, six male and four female. These listeners were selected from a standby group of about 35 volunteers, mostly graduate students, who regularly serve as listeners for measurements of this kind.

The measurements were made in a room designed for this purpose. All acoustic characteristics of the room meet the requirements outlined in ANSI S3.19-1974. The ambient noise levels in this room are below the limits specified in ANSI S3.19-1974, and open ear thresholds are used on a continuing basis to monitor the background noise levels. An automatic recording attenuator was used to record both open and occluded ear thresholds.


Each of ten subjects was tested three times at each of nine test frequencies. The attached Tables show grand mean attenuation values in decibels (dB) for each test signal along with group attenuation values. Standard deviations (S.D.) for the 30 different attenuation determinations for each test signal are also given. The results presented in this report pertain to the samples tested only.

accredited by the National Institute of Standards and Technology (NIST) National Laboratory Accreditation Program (NVLAP) for tests performed according to ANSI S3.19-1974, ANSI S12.6-2008 and AS/NZ S1270:2002. These accreditation criteria encompass the requirements of international standard ISO Guide 17025. This report may only be reproduced or transmitted electronically in its' entirety. This report shall not be used to claim product endorsement by NIST, NVLAP or by any agency of the U.S. Government. All measurement equipment are calibrated with instrumentation traceable to the NIST.

Use these laboratory-derived attenuation data for comparison purposes only. The amount of protection afforded in field use is often significantly lower depending on how the protectors are fitted and worn.



Kevin Michael, Ph.D.
President



Date

Individual and Summary Attenuation Data for
Hearing Protective Devices

Test Method: ANSI S3.19-1974

Position: Insert

Date: 10/23/12

Model: Metal Detectable Polyurethane Foam Ear Plug

FREQUENCY IN HERTZ

SUBJECT	125	250	500	1000	2000	3150	4000	6300	8000
1	46	39	48	47	35	38	41	45	43
	45	40	49	46	34	34	45	42	40
	45	39	50	46	40	40	40	43	42
2	43	42	48	46	41	45	49	53	49
	36	36	35	36	36	37	41	51	50
	42	41	47	45	41	45	46	51	50
3	41	37	39	37	38	47	49	53	51
	41	32	40	35	38	48	51	52	50
	40	36	40	35	36	49	52	49	52
4	38	34	41	40	40	43	48	46	47
	37	35	40	39	31	43	45	48	50
	37	37	45	37	37	43	47	50	51
5	36	41	47	37	36	41	41	44	53
	39	37	42	41	39	45	46	46	58
	33	39	46	44	41	46	46	44	48
6	41	42	46	36	40	48	52	46	45
	39	39	43	41	39	49	53	48	47
	39	37	41	41	40	48	54	49	46
7	33	28	38	38	36	46	43	39	40
	32	29	37	38	35	46	44	41	42
	36	35	38	38	35	46	44	43	42
8	31	31	39	36	40	39	43	49	46
	34	34	38	35	40	41	43	49	47
	35	32	37	36	40	38	44	50	47
9	41	37	44	45	40	48	52	56	57
	41	35	45	46	42	48	51	56	55
	41	36	47	46	41	46	50	55	56
10	39	41	42	43	39	44	44	49	49
	40	42	44	41	40	44	45	50	50
	40	40	44	40	42	46	47	51	48
MEANS	38.6	36.8	42.6	40.3	38.4	44.1	46.5	48.3	48.3
STD. DEV.	3.8	3.9	4.1	4.0	2.6	3.9	4.0	4.4	4.7

NRR = 32 dB

Use these laboratory-derived data for comparison purposes only. The amount of protection afforded in field use is often significantly lower depending on how the protectors are fitted and worn.

Date: 10/23/12

Model: Metal Detectable Polyurethane Foam E.
Position: Insert

Measurements were made according to American National Standards Institute Specifications ANSI S3.19-1974.

Center Frequency in Hz	Mean Attenuation in dB	Group Attenuation in dB	Standard Deviation in dB
125	38.6	75.4	3.8
250	36.8		3.9
500	42.6		4.1
1000	40.3		4.0
2000	38.4	211.9	2.6
3150	44.1		3.9
4000	46.5		4.0
6300	48.3	96.5	4.4
8000	48.3		4.7

