

VeriShield™ VS130N Passive Earmuff

Honeywell

HOWARD
LEIGHT

PRODUCT INFORMATION

Rev.:
01

Date:
2019.06.20

SPECIFICATIONS

ARTICLE		VeriShield Passive Behind-the-Neck Earmuff, VS130N	
MODEL NO		1035116-VS	1035117-VS
REGION		Americas	EMEA/AUS
BARCODES	Box	7312550351161	7312550351178
	Case	17312550351168	17312550351175
WEIGHT		251g	251g
ACCESSORIES	Hygiene Kit	1035138-VS	1035138-VS
	Cool Pads	1000365	1000365
SALES UNITS	Box	1 EA	1 EA
	Case	10 boxes	10 boxes
VOLUME	Box	L165*W120*H150mm	L165*W120*H150mm
		2.97dm ³	2.97dm ³
	Case	L615*W345*H182mm	L615*W345*H182mm
		38.62dm ³	38.62dm ³
MATERIAL	Box	Cardboard	Cardboard
	Case	Corrugated cardboard	Corrugated cardboard



POS.	PART LISTING	MATERIAL	COLOR
1	Ear Cup	ABS	NCS 8500-N
2	Rim	PP	NCS 8500-N
3	O-ring	Silicon	NATURAL
4	Foam Insert	PU foam	PMS 7621C
5	Ear Cushion	PVC/PU Foam	NCS 9000-N
6	Wire Guide	POM	NCS 9000-N
7	Headband	PU/Steel	NCS 9000-N

VeriShield™ VS130N Passive Earmuff

Honeywell

HOWARD
LEIGHT

PRODUCT INFORMATION

Rev.:
01

Date:
2019.06.20

CUSTOM TARIFFS

39269099

COUNTRY OF ORIGIN

China

TEMPERATURE OPERATION RANGE

0°C to +55°C/32°F to +131°F

PRODUCT MARKING

"Honeywell HOWARD LEIGHT" - cup

"VS130N" – cup

NRR

VeriShield™ VS130N Passive Earmuff is tested according to ANSI S3.19-1974 at Michael & Associates Inc.

Frequency Hz	125	250	500	1000	2000	3150	4000	6300	8000	NRR
Mean Value, dB	21.8	25.0	31.5	37.8	38.2	38.6	39.5	39.3	39.4	28 dB
Standard Deviation, dB	2.4	2.5	2.3	2.4	2.0	2.9	3.6	2.5	3.9	
CSA Class AL	Clamping force: 2.9 lbs									

SNR

VeriShield™ VS130N Passive Earmuff is tested according to EN 352-1:2002 at Michael & Associates Inc.

Frequency Hz	125	250	500	1000	2000	4000	8000	SNR
Mean Value, dB	22.5	24.8	31.4	36.9	36.5	37.9	38.9	
Standard Deviation, dB	2.6	2.9	2.8	2.5	2.8	3.4	2.8	33 dB
APV, dB	19.9	21.9	28.6	34.4	33.7	34.5	36.2	
H=35 dB M=31 dB L=25 dB	Clamping force: S/9.6N M/12.3N L/13.2N							

SLC80

VeriShield™ VS130N Passive Earmuff is tested according to AS/NZS 1270:2002 at Michael & Associates Inc.

Frequency Hz	125	250	500	1000	2000	4000	8000	SLC80
Mean Attenuation, dB	20.1	22.4	30.3	35.5	35.5	36.0	38.0	
Standard Deviation, dB	4.1	4.1	3.6	3.3	3.8	3.1	3.4	31 dB
Mean-Minus-Std Deviation, dB	16.0	18.3	26.7	32.2	31.7	32.9	34.6	
Class 5	Clamping force: S/12.9N M/13.3N L/12.5N							

Distributed by:

NELSON JAMESON

INC.

800-826-8302 nelsonjameson.com