


# BSX900

## Compact Walk-Through Boot Scrubber Unit w/ Dual Sole Brushes

The BSX900 is a wet, compact walk-through, sole-only, dual boot scrubber. The user activates the system by stepping onto the platform. Diluted cleaning solution is sprayed onto rotating brushes and transferred onto the boots from a stainless steel venturi dilution valve and metering tip to provide the desired PPM. The BSX900 uses two rotating horizontal sole brushes, has a small footprint, and is ideal for tight spaces and medium traffic applications.

### Features

- Compact design for 1 user at a time (15-25 users per minute)
- Solid member stainless steel construction with hinged access grate
- Two removable anti-slip steps
- Bi-directional entry / exit with central emergency stop
- Wash-down rate stainless electrical enclosure, motors, and hardware
- Spray nozzles directed down to prevent over-spray, coating brush prior to boot contact
- Open grate design ensures optimal debris management
- Proximity sensor and spring loaded grate for unit activation with adjustable timer
- Self-draining tub with 2.5" tri-clamp fitting and four adjustable dairy approved feet
- Solenoid activated brush spray system and venturi injector with 1.5 gpm flow rate
- Optional side shields available for additional splash or overspray prevention



### Connection Requirements

- Electrical Options:
  - 115VAC, single phase, 60Hz, 19.1A
  - 230VAC, single phase, 60Hz, 13.7A
  - 480VAC, triple phase, 60Hz, 3.9A
- 3/8" Nptf cold water connection, 50psi recommended
- 2 1/2" Tri-clamp drain connection



Use Alpet® No-Rinse Quat Sanitizer with the BSX900 to aid in the cleaning of footwear prior to sanitization.

Throughput	Where to Use
<ul style="list-style-type: none"> <li>• 1 user at a time</li> <li>• 15-25 users per minute</li> </ul>	<ul style="list-style-type: none"> <li>• Plants with lower number of employees</li> <li>• Plants with limited/medium open space</li> <li>• Areas with access to water lines</li> <li>• Areas with accessible floor drains</li> </ul>
<b>Dimensions</b> Height 63" x Width 45" x Length 54"	<b>Weight</b> 425 LB

- BSX900-DAF-115V Boot Scrubber w/ Dairy Approved Feet - 115VAC, single phase
- BSX900-DAF-230V Boot Scrubber w/ Dairy Approved Feet - 230VAC, single phase
- BSX900-DAF-480V Boot Scrubber w/ Dairy Approved Feet - 480VAC, triple phase