

Distributed by:



800-826-8302 nelsonjameson.com

USER MANUAL

**MODEL NUMBER:
FI-10N-SM
FI-10NK-SM
FI-10NV-SM
AND RELATED UNITS**

10 Gallon Smart Foam Unit

English (Original Instructions)

READ ALL INSTRUCTIONS BEFORE OPERATING EQUIPMENT



WARNING



Read this manual completely and understand the machine before operating or servicing it.

- Read all instructions before installing or operating unit.
- Always wear appropriate personal protective equipment (PPE) when operating or servicing unit.
- Always follow all chemical safety precautions and handling instructions provided by the chemical manufacturer and Safety Data Sheet (SDS).
- If this unit is modified or serviced with parts not listed in this manual, the unit may not operate correctly.
- Never point the discharge wand at yourself, another person, or any object you do not want covered in chemical.
- Always keep the air trigger port clean and free of blockages or debris. If the port becomes dirty or blocked, disconnect the compressed air source from the unit immediately and clean out the port before proceeding.
- Always keep the discharge hose free of kinks or obstructions.
- Always rinse and drain unit after use (as described in the After Use Instructions). Always store unit disconnected from the compressed air source.
- Do not exceed an incoming air pressure of 100 psi (7 bar).
- Do not exceed a fluid temperature of 100°F (37°C).
- Always flush the unit with fresh water for 5 minutes when switching from an alkaline to an acid or an acid to an alkaline.
- Only use clean and dry air. Air must be filtered and free of moisture or pump life will be diminished. If needed, install a water separator (WS-20CFM) before the unit.
- Do not use an air lubricator before the unit.

PROTECT THE ENVIRONMENT

Please dispose of packaging materials, old machine components, and hazardous fluids in an environmentally safe way according to local waste disposal regulations.



Always remember to recycle.

*Specifications and parts are subject to change without notice.

| OPTIONS | | |
|---------|--------------------------------|-----|
| | Pump Seal Material | |
| FI-10N | Santoprene (standard) | -SM |
| | Viton (V) | |
| | Kalrez (K) | |

Add bold option codes to item number as shown. For standard options, no option code is needed.

Examples:

- FI-10N-SM (standard unit with Santoprene pump seals)
- FI-10NV-SM (unit with Viton pump seals)

READ ALL INSTRUCTIONS BEFORE OPERATING EQUIPMENT

| REQUIREMENTS | |
|-----------------------------|--|
| Compressed air requirements | 40-80 psi (3-5 bar) with 5-10 cfm (141-283 l/min) |
| Liquid temperature range | 40-100°F (4.4-37°C) |
| Chemical compatibility | Chemical products used with this equipment must be formulated for this type of application and compatible with unit materials and pump seals. For more information on chemical compatibility, consult the manufacturer or SDS for your product or contact our customer service department. |

| SPECIFICATIONS | |
|---------------------------------------|---|
| Power type | Compressed air |
| Chemical pickup type | Draws from pre-mixed solution |
| Number of products unit can draw from | One product |
| Capacity | 12.5 gallons (47.3 liters) |
| Discharge hose diameter/length | 20 ft. (9.1 m) bonded hose, with 5/8 in. (15.9 mm) and 1/4 in. (6.4 mm) inside diameter |
| Discharge wand/tip type | Ultra high molecular weight (UHMW) polyethylene handle and wand extension, with 65 fan tip and built-in zero tip |
| Output distance | With zero tip: 17-21 ft. (5.2 m – 6.4 m) With fan tip (ST65150): 16-20 ft. (4.9 m – 6.1 m) |
| Output volume | With zero tip: 20-32 gal/min (75-121 l/min) of foam With fan tip (ST65150): 20-32 gal/min (75-121 l/min) of foam |
| Flow rate* | 2 gal/min (7.6 l/min) |
| Pump seals | Santoprene, Viton, or Kalrez |
| Wheel type | Two 10 inch non-marking wheels |

*Dilution rates and flow rates given are based on chemical with viscosity of water and factory air pressure settings.

READ ALL INSTRUCTIONS BEFORE OPERATING EQUIPMENT

Operation Instructions:

1. Verify that the drain plug (DP-A) is securely closed.
2. Follow all instructions from the chemical manufacturer. Fill the tank with water and the advised percentage of chemical concentrate.
3. Verify that the valve (PVCV34FM) at the base of the suction line is open, to allow fluid into the suction line.
4. Verify that the air trigger port is clean and free of blockages or debris, and the discharge hose is not kinked or obstructed.
5. With the wand pointed in a safe direction, connect an air line to the air inlet fitting (AP25).
Note: When you connect the air line, listen for any sound from the unit. If you hear the pump activate and begin to cycle, disconnect the air line immediately. This indicates that there is a blockage or other problem somewhere in the system, which could cause the unit to activate spontaneously. The problem must be addressed before proceeding (see "Troubleshooting Instructions").
6. Place thumb over the air trigger to activate the unit and begin foaming.
7. While the unit is running and discharging product, adjust the needle valve (NV14Y) as needed to regulate the wetness or dryness of the foam following the steps below:
 - a. Close needle valve completely in clockwise direction.
 - b. Open needle valve in counter-clockwise direction 2 complete turns.
 - c. Continue to open needle valve in ¼ turn increments, allowing 30 seconds between adjustments, until desired consistency of foam is achieved.
8. Release the air trigger to stop foaming.
Note: When you release the air trigger, the unit will shut off and depressurize. Foam that is already in the discharge hose may seep out, but no more foam will be created until you cover the air trigger again.

After Use Instructions:

1. Open the drain plug (DP-A) and drain the unit tank.
2. Rinse the unit tank thoroughly with fresh water. Then replace the drain plug and fill the tank with fresh water.
3. Activate the unit and allow it to run for 2-4 minutes, or until all chemical has been flushed from the system.
4. Open the drain plug (DP-A) and drain any water remaining in the unit tank. Then replace and secure the drain plug.
5. Disconnect the air line from the air fitting (AP25).
6. Allow any liquid remaining in the discharge hose to drain out through the discharge wand before storing the unit.

Maintenance Instructions:

To keep your unit operating properly, periodically perform the following maintenance procedures:

Note: Before performing any maintenance, ensure that the unit has been disconnected from the air supply according to the "After Use Instructions." Also ensure that the unit tank is empty, and/or close the valve (PVCV34FM) at the base of the suction line to shut off the flow of liquid from the tank. Reopen the valve after maintenance is complete.

- Inspect the air pump (P56/P56K/P56V) for wear and leaks.
- Inspect all hoses for leaks or excessive wear. Make sure all hose clamps are in good condition and properly secured.
- Check the air trigger port on the handle for debris and clean as needed. When cleaning, be careful not to push debris into the port, as it may become lodged inside and create a blockage.
- Clean and replace the filter (AFR25) located within the air regulator (R25) as needed. Access the filter by unthreading the air regulator bowl (ABR25) from the air regulator (R25).
- Check the suction line and strainer (STR38-IL) for debris or blockages, and clean as needed.
- Drain your air compressor tank on a regular basis to help extend pump life. An air source with a high moisture content will accelerate pump wear. **Note:** If your air source has a high moisture content, you may wish to install a water separator (WS-20CFM) before the unit.


READ ALL INSTRUCTIONS BEFORE OPERATING EQUIPMENT

Troubleshooting Instructions:


- Check to ensure that the discharge hose is uncoiled properly, and that there are no kinks that could obstruct fluid flow.
- Check the suction line and strainer for debris or damage. Clean or replace as needed. To prevent damage to the unit, the strainer (STR38-IL) must always be used.
- If the pump is cycling but will not pull product, and the suction line is clear, make sure the valve (PVCV34FM) at the base of the suction line is open.
- Check the air regulator bowl (ABR25) and air filter (AFR25) for debris such as water, oil, or rust particles. Clean by unthreading the air regulator bowl (ABR25) from the air regulator (R25).
- If the needle valve (NV14Y) is open too far, the pump (P56/P56K/P56V) may cycle improperly due to lack of air pressure. If this occurs, close and readjust the needle valve (NV14Y) as described in the Operation Instructions.
- Make sure proper foaming chemical and concentration are being used.
- If air passes through the pump (P56/P56K/P56V) without cycling, the pump needs to be replaced.
- If solution backs up into the air regulator bowl (ABR25), the check valve (CV38) needs to be replaced.
- If foam comes out wet, no matter where the needle valve (NV14Y) is positioned, the check valve (CV38) may need to be replaced.
- Check for proper air pressure on the air gauge (AG100). The air regulator (R25) is factory set at 50 psi (3.4 bar). Operating range is 40 to 80 psi (3 to 5 bar) with 5 to 10 CFM (141.6 to 283.3 l/min).
- If the unit operates at a reduced pressure:
 1. Check the air compressor supplying the unit. If the pressure is less than 40 psi, turn the unit off until the compressor can catch up.
 2. If the air supply is 50 psi (3.4 bar) or above, check the air gauge (AG100), which should read near 50 psi (3.4 bar). If the air gauge reads more or less than 50 psi (3.4 bar), adjust the pressure by turning the knob on the top of the air regulator (R25).
 3. If the problem persists, the stainless steel mixing mesh (SS-MESH) inside the tee fitting (SST12HB38) could be plugged. Remove and clean the mesh following the instructions below:
 - a. Ensure that the unit has been flushed and disconnected from the air supply according to the "After Use Instructions." Also ensure that the unit tank is empty, and/or that the valve (PVCV34FM) at the base of the suction line is closed.
 - b. Remove the stainless hose barb (HBSS1258) from the tee fitting (SST12HB38).
- c. The stainless steel mixing mesh (SS-MESH) is located inside the tee fitting (SST12HB38). Remove the old mesh and the screen that holds it in place. If the mesh and screen are in good condition, they can be cleaned and re-used. If not, they should be replaced with new parts.
- d. Insert the new mesh (SS-MESH).
- e. Insert the new screen (SSST). Make sure it is seated securely, but not bent or deformed.
- f. Reconnect the hose barb (HBSS1258) to the tee fitting (SST12HB38). Attach the 5/8 inch hose to the hose barb (HBSS1258) and secure it with the screw band clamp (SSC58).
- g. If you found a lot of particles or blockages inside the mesh, check the suction line strainer (STR38-IL) to make sure it is in place and operating correctly.
- If the unit activates when the air trigger port is not covered:
 1. Verify that the air trigger port is clean and free of blockages or debris, and the discharge hose is not kinked or obstructed.
 2. If the problem persists, try bypassing the air trigger. To do this, disconnect the 1/4 inch hose from the wand. Point the wand in a safe direction and connect an air line to the unit. Then, use your thumb or finger to seal the open port of the 1/4 inch hose at the wand.
 - a. If the unit activates when you connect the air line, the valve block (SM-PV) may need to be replaced.
 - b. If the unit does not activate when you connect the air line, the hose or wand assembly may need to be replaced.
- If the unit does not activate when the air trigger port is covered:
 1. Confirm the incoming air supply is consistently 50 psi (3.4 bar) on the air gauge (AG100).
 2. If the problem persists, the valve block (SM-PV) may need to be replaced.

READ ALL INSTRUCTIONS BEFORE OPERATING EQUIPMENT


TANK ASSEMBLY ITEM NUMBER: TANK-10N-A



WAND ASSEMBLY ITEM NUMBER: SMWA




DISCHARGE HOSE ASSEMBLY ITEM NUMBER: H5814-20




READ ALL INSTRUCTIONS BEFORE OPERATING EQUIPMENT

BACK PLATE


ITEM NUMBER: PA-PF-SM



BACK PLATE Outside View




READ ALL INSTRUCTIONS BEFORE OPERATING EQUIPMENT



OPTIONAL HOSE ATTACHMENT (INCLUDED)
ITEM NUMBER: SM-EA

- Installation Instructions
1. Remove wand (PW1238) from handle (SMH)
 2. Thread HBSS1258 from hose attachment into handle (SMH)
 3. Thread wand (PW1238) onto coupler (SC1212) at the end of hose attachment.

| ITEM NUMBER | |
|-------------|--|
| EC58 | OETIKER CLAMP 0.625 ID |
| H58-6 | 6 FT. OF 5/8 INCH BLUE HOSE |
| HBSS1258 | STAINLESS STEEL HOSE BARB 1/2 MPT BY 5/8 INCH BARB |
| SC1212 | S.S. COUPLER 1/2in BY 1/2in |



READ ALL INSTRUCTIONS BEFORE OPERATING EQUIPMENT

| ITEM NUMBER | DESCRIPTION | | |
|-------------|---|----------------|--|
| AG100 | 1.5 INCH DRY MODEL 20 DUAL SCALE GAUGE | P56 | PUMP WITH SANTOPRENE SEALS - INCLUDES HOSE BARBS, AIR FITTING, AND EXHAUST BARB |
| AP25 | PLUG 1/4 NPTM AIR FITTING - BRASS | P56K | PUMP WITH KALREZ SEALS - INCLUDES HOSE BARBS, AIR FITTING, AND EXHAUST BARB |
| AS1-VS | 1/4-20 X 1/2 PHIL TRUSS MACH SCREW 19-8 W/516 ORANGE VIBRASEAL PATCH | P56V | PUMP WITH VITON SEALS - INCLUDES HOSE BARBS, AIR FITTING, AND EXHAUST BARB |
| B8X58 | 8-15 x 1/2 FLAT PHIL TY-A 18-8 PLN | 20756103B | Polypro G57 Air Port x HB Straight, w/ Viton o-ring |
| BPS-58SO | Back Panel Screw - 5/8 inch with Stand Off | HB14P | 1/4in BRASS HB AIR FITTING /G57/P56 |
| BPS-SSR | 1/4 INCH PUSHNUT BOLT RETAINER STAINLESS STEEL | HB5638 | HOSE BARB FOR P56 PUMP |
| BX-10N | 18-1/2 x 16 x 42 Glued Inside Joint ECT 48 | HB5638K | HOSE BARB FOR P56K PUMP |
| COT | 1/8 X 1 COTTER PIN 18-8 S/S | HB5638V | HOSE BARB FOR P56V PUMP |
| CV38 | PVC CHECK VALVE 3/8 BARBS - SS SPRING | P56-BRKT | PUMP BRACKET- STAINLESS STEEL |
| DFP7 | 7 INCH HINGED CAP ASSEMBLY - INCLUDES BLACK CAP, LID FLANGE AND HINGE PIN | P56-BRKT-SCREW | HI LO SCREW FOR RETAINING P56-BRKT |
| DFP7-C | 7 INCH FILL CAP POLYETHYLENE BLACK | PLPF | PORTABLE FOAMER BACK PLATE W/ HINGE AND HOLES |
| DFP7-F | 7 INCH TANK LID FLANGE POLYETHYLENE | PLPF-PIN | 302 STAINLESS PORTABLE PLATE HINGE PIN |
| DFP7-PIN | HINGE PIN FOR DFP7-C & DFP7-C | PVCV34FM | PVC VALVE 3/4in FPT X 3/4in MPT |
| DFP7-C-BL | 7 INCH FILL CAP POLYETHYLENE BLUE PANTONE | PW1238 | POLY WAND - 1/2 MPT X 3/8 FPT - UHMW |
| DFP7-C-GN | 7 INCH FILL CAP POLYPRO GREEN PANTONE | R25 | AIR REGULATOR - 1/4fpt TWO PORT 1/8fpt TWO PORT - INCLUDES FILTER AND BOWL |
| DFP7-C-RD | 7 INCH FILL CAP POLYPRO RED PANTONE | ABR25 | METAL AIR BOWL for R25 |
| DFP7-C-YL | 7 INCH FILL CAP POLYPRO YELLOW PANTONE | AFR25 | AIR FILTER for R25 |
| DP-A | DRAIN PLUG ASSEMBLY FOR NATURAL PORTABLE UNITS | S142058-VS | 1/4-20 X 5/8 PHIL TRUSS MACHINE SCREW 18-8 W/#516 VIBRASEAL ORANGE PATCH |
| DP | FRONT DRAIN PLUG FOR PORTABLE UNIT POLYETHYLENE | SC1212 | S.S. COUPLER 1/2in BY 1/2in |
| DP-G | FKM LATHE CUT 60 DUROMETER FKM | SM-PV | PNEUMATIC VALVE FOR SMART TECHNOLOGY UNITS |
| EC14-2 | OETIKER CLAMP 13.8 | SMH | HANDLE FOR BONDED HOSE - 1/2in FPT AND 1/8in FPT - UHMW |
| EC58 | OETIKER CLAMP 0.625 ID | SN1414 | STAINLESS 1/4MPT X 1/4MPT NIPPLE |
| FWAX15 | FLAT AXLE WASHER | SSA14 | SS304 MALE/FEMALE ADAPTOR 1/4 NPT X 1/4 NPT |
| FWP12 | 7/8 ID X 1.5 OD X 0.05 THK SSFW | SSAXLE14 | 14 ½" long with the 5/8" diameter bar & 2 through holes with countersinks beveled ends |
| FWP14 | C-816 1/2in SS WASHER | SSC14 | WORM GEAR CLAMP, SS 1/4IN |
| H14B-H | 1/4 INCH BLUE HOSE - Available per ft. | SSC38 | WORM GEAR CLAMP, S/S (.25-.63) |
| H38B-H | 3/8 INCH BLUE HOSE - Available per ft. | SSC58 | WORM GEAR CLAMP, SS 5/8IN |
| H5814 | BONDED HOSE 5/8in ID - 1/4in ID | SSP12 | STAINLESS STEEL AXLE PLATE - 2.5 inch X 1 inch - 2 HOLE |
| H58-6 | 6 FT. OF 5/8 INCH BLUE HOSE | SST12HB38 | STAINLESS TEE COMBO 1/2in FPT X 3/8 in BARB WITH SSST AND S.S. MESH |
| HBEL1414 | 1/4 MPT X 1/4 HOSE BARB BRASS 90 DEG | SS-MESH | STAINLESS STEEL MESH WITH SSST FOR REPLACEMENT |
| HBSS1258 | STAINLESS STEEL HOSE BARB 1/2 MPT BY 5/8 INCH BARB | SSST | SCREEN DISC .687 DIA. 10 X 10 MESH @ .020 DIA. 300 SERIES S.S. |
| HBSS1414 | HOSE BARB STAINLESS STEEL 1/4 MPT X 1/4 BARB | ST65150 | VEEJET NOZZLE 65150 - 3/8 MPT |
| HBSS1438 | STAINLESS HOSE BARB 1/4 MPT X 3/8 BARB | STR38-IL | IN LINE STRAINER 3/8 BARB 20 MESH 304 STAINLESS EDPM GSKT |
| HBSS1814 | 1/8 MPT X 1/4 STAINLESS HOSE BARB | TANK-10N | 10 GALLON NATURAL TANK |
| HBSS1438 | STAINLESS HOSE BARB ELBOW 1/4 INCH NPT X 3/8 HOSE BARB | TW916 | 1/2 INT TOOTH L/W 410SS |
| HHPB3414 | HEX HEAD POLY REDUCER BUSHING 3/4 X 1/4 | W15 | NONMARKING WHEEL FOR PORTABLE UNITS |
| NV14Y | FLOW CONTROL VALVE - INCLUDES BLACK KNOB | | |
| NV14Y-HNDL | BLACK KNOB FOR NEEDLE VALVE - 2839-1/4 | | |
| P18 | PLUG 1/8 MPT HEX HEAD 304 SS | | |