



TECHNICAL DATA SHEET

Sift-Socks™ Nylon Connectors

Distributed by:



800-826-8302 nelsonjameson.com

RUBBER-COATED NYLON (RCN)

Very pliable soft rubber coating on a two-way nylon backing. The rubber portion of the rubber coated nylon fabric is in compliance with FDA requirements of CFR 21.177.2600 (Rubber Articles Intended for Repeated Use).



FDA ACCEPTABLE MATERIALS

FIBER CONTENT	NEOPRENE WITH NYLON BACKING
MATERIAL	RUBBER COATED NYLON
WEIGHT	32 OUNCES/YD2 / 678 G/M2
PERMEABILITY	0 CFM @ 0.5" WATER GAUGE
TEMPERATURE RANGE	0° TO 200° F CONTINUOUS, 250° F MAX -18° TO 93° C CONTINUOUS, 121° C MAX

DISCLAIMER: THE DATA PROVIDED IS INTENDED AS A GUIDE ONLY AND SHOULD NOT BE INTERPRETED AS A WARRANTY. IT IS NOT INTENDED TO BE USED TO DETERMINE THE SUITABILITY OF THE PRODUCT FOR ANY SPECIFIC CUSTOMER APPLICATION. SIFTEX STRONGLY SUGGESTS THAT EACH CUSTOMER THOROUGHLY TEST THE PROSPECTIVE PRODUCT IN THEIR OWN MANUFACTURING FACILITY TO DETERMINE THE ACTUAL SUITABILITY OF THE PRODUCT IN THEIR SPECIFIC APPLICATION.

Siftex is focused on helping you spend less time with downtime by providing the innovative products, personal attention, superior customer service and on-time deliveries you expect.

