

Versilon[™] PSD Hose

Suction and Discharge Rubber Hose

Saint-Gobain Performance Plastics' Versilon PSD hose is constructed with a white FDA compliant chlorobutyl inner core and has an EPDM cover reinforced with two fabric spirals and a galvanized helix wire. The abrasion resistant cover of PSD helps maintain a clean appearance. PSD hose is designed to reduce the risk of taste and odor adulteration of fine food and beverage products and is highly resistant to common CIP solutions.

Versilon PSD hose has been carefully engineered to handle a wide variety of product and application requirements. PSD is rated for full suction and discharge service up to 150 psi. Our unique reinforced fabric spiral and wire helix design gives PSD exceptional flexibility for handling ease.

Features and Benefits

- Engineered to handle a wide variety of applications
- Rated for full suction and discharge service up to 150 psi
- Unique reinforced fabric spiral and wire helix design delivers exceptional flexibility

Typical Applications

- Cosmetics
- Personal care
- Food and beverage
- Dairy

Regulatory Compliance

- Compliant with FDA 21CFR 177.2600
- USDA
- 3-A Sanitary Standard 62-02

PSD Hose Specifications

Part Number	Inside Diameter		Outside Diameter		Maximum Working Pressure		Minimum Bend Radius		Vacuum Hg		Weight	
	(in)	(mm)	(in)	(mm)	(psi)	(MPa)	(in)	(mm)	(in)	(mm)	(lb/ft)	(kg/m)
GRAY COVER												
PSD050	1/2	12.7	1-1/32	26.2	150	1.03	2.00	50.8	29	736.6	0.40	0.60
PSD075	3/4	19.1	1-8/32	31.8	150	1.03	3.00	76.2	29	736.6	0.56	0.83
PSD100	1	25.4	1-17/32	38.9	150	1.03	4.00	101.6	29	736.6	0.65	0.97
PSD150	1-1/2	38.1	2-5/32	54.8	150	1.03	6.00	152.4	29	736.6	1.07	1.59
PSD200*	2	50.8	2-21/32	67.5	150	1.03	7.00	177.8	29	736.6	1.43	2.13
PSD250	2-1/2	63.5	3-6/32	81.0	150	1.03	8.00	203.2	29	736.6	2.08	3.10
PSD300*	3	76.2	3-24/32	95.3	150	1.03	9.00	228.6	29	736.6	2.63	3.91
PSD400*	4	101.6	4-24/32	120.7	150	1.03	12.00	304.8	29	736.6	3.13	4.66
PSD600	6	152.4	6-24/32	171.5	150	1.03	36.00	914.4	29	736.6	5.22	7.77
WHITE COVER												
PSD150-W	1-1/2	38.1	2-5/32	54.8	150	1.03	6.00	152.4	29	736.6	1.07	1.59
PSD200-W	2	50.8	2-21/32	67.5	150	1.03	7.00	177.8	29	736.6	1.53	2.28
PSD300-W	3	76.2	3-24/32	95.3	150	1.03	9.00	228.6	29	736.6	2.63	3.91

NOTE: Weights and outside diameter dimensions are nominal. Data given is for hose only. End fitting vs. hose pressure limitations must be considered and the lower of the two ratings must be used on assemblies. Pressure ratings are shown at ambient temperature (68°F). As temperature increases, working pressure and vacuum ratings will decrease. Contact factory for recommendation for assembly applications that exceed 200°F.

* Heavy duty construction

Construction

Inner Tube:	White chlorobutyl			
Cover:	EPDM			
Reinforcement:	Two fabric spirals with galvanized helix wire (carbon steel for the 6" size)			
Color:	Gray with a blue layline in black lettering or white with a blue layline in black lettering			
Temperature Rating:	-40°F to +225°F (continuous) +250°F (intermittent) -40°C to +107°C (continuous) +121°C (intermittent)			
Maximum Length*:	1/2" 3/4" 1" 1-1/2" 2"	100' 100' 100' 100' 100'	2-1/2" 3" 4" 6"	100' 100' 100' 20'

*Special order up to 400ft. length

Fitting Options

Versilon ReSeal® Reusable Fittings

- Available in 11 standard end styles (Other end styles available)
- Stems are manufactured from grade 316L stainless steel with an average interior surface finish as low as 15Ra
- Hose sleeves are available in either stainless steel or high impact polymer

Versilon Crimp Style Fittings

- Over 40 styles of stocked crimp-style fittings in a wide range of materials
- Standard: 316L stainless steel (wetted surfaces)

Limited Warranty: For a period of 6 months from the date of first sale, Saint-Gobain Performance Plastics Corporation warrants this product(s) to be free from defects in manufacturing. Our only obligation will be to provide replacement product for any portion proving defective, or at our option, to refund the purchase price thereof. User assumes all other risks, if any, including the risk of injury, loss or damage, whether direct or consequential, arising out of the use, misuse, or inability to use this product(s). SAINT-GOBAIN DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.



Saint-Gobain Performance Plastics

1600 Cottontail Lane
Somerset, NJ 08873

1-800-435-3992

Tel: (732) 652-0910

Fax: (732) 764-3871

www.processsystems.saint-gobain.com



NOTE: Saint-Gobain Performance Plastics Corporation does not assume any responsibility or liability for any advice furnished by it, or for the performance or results of any installation or use of the product(s) or of any final product into which the product(s) may be incorporated by the purchaser and/or user. The purchaser and/or user should perform its own tests to determine the suitability and fitness of the product(s) for the particular purpose desired in any given situation.

Versilon™ is a trademark of Saint-Gobain Performance Plastics.