

Technotes

Highlighting technical features for
Thermo Scientific™ Precision™ Refrigerated Incubators

Temperature Uniformity Features

- Microprocessor control with easy-to-read display shows temperature within 0.1°C
- Push-button controls for temperature setpoint selection
- Forced-air circulation designed to deliver outstanding temperature stability
- RTD temperature probe and protected setpoint mode designed to prevent accidental temperature change

Why choose a Precision refrigerated incubator for your lab?

Ideal for applications that require temperatures ranging from -10 °C to +60 °C



566L (20. cu.ft) Precision refrigerated incubator

Efficient Design Features

- Easy-to-clean, corrosion-resistant construction
- Compressor relay designed to conserve energy*
- Chlorofluorocarbon (CFC)-free, foamed polyurethane insulation designed to prevent heat loss

173L (6.1 cu. ft.) Unit

- Economical under-counter design
- High/low safety thermostat backups
- Three cooling modes simplify operation: high precision with cooling; high precision without cooling; and frost-free with variable cooling
- Four adjustable leveling feet for stable setup
- 2A outlet easily supports apparatus inside the unit

566L (20 cu. ft.) Unit

- Ideal for BOD (biochemical oxygen demand) applications and temperature settings at or below ambient
- Holds over 300 BOD bottles (300mL)
- Temperature setpoint selection with high/low temperature protection and simple calibration
- Energy efficient design, cooling can be switched off for temperatures above ambient - energy consumption as low as 0.1kW at 37 °C*
- Safety relay and alarm LED alert to over/undertemperature conditions
- RS-232 and recorder jacks for data logging
- Standard access port for feeding probes and apparatus cord in/out of unit (Ø 30mm/1.2in.)
- Lockable door designed to protect samples

Plant Growth Unit with Light - 504L (17.8 cu. ft.)

- Programmable temperature and light cycles: 7-day program with 2 light cycles per day
- Dual-lamp fluorescent lighting provides 342-foot candles (3678 Lux) for uniform illumination

Refrigerated Incubators—Warranty: 2 year (parts and labor)**; certifications: 115/120V units are cCSAus listed
Plant Growth Model—Warranty: 1 year (parts and labor)**; certifications: 120 V unit cCSAus listed

*Based on internal testing.

**Subject to terms of manufacturer's standard limited warranty, available at www.thermoscientific.com.



173 L (6.1 cu. ft) Precision refrigerated incubator

Thermo
SCIENTIFIC

Thermo Scientific Precision Refrigerated Incubators



504L (17.8 cu. ft.)
Precision plant growth model

Application Information

Various models designed to provide stable conditions for the following applications:

- BOD determination
- Sample storage - below and above ambient temperature
- Bacterial research
- Mycology studies
- Fish or insect breeding
- Seed germination
- Plant growth

Specifications							
Cat. No.	Capacity	Shelves	Interior Dimensions (D x W x H)	Exterior Dimensions (D x W x H)	Uniformity @37 °C/20 °C	Temp. Range	Electrical
BOD models							
PR205745R	173L (6.1 cu. ft.)	2 supplied/4 max	520 x 520 x 700mm (20.5 x 20.5 x 28in.)	622 x 610 x 876mm (24.5 x 24 x 34.5in.)	± 0.6/1.0 °C*	-10° to +60 °C	115V 60Hz (9.5A), NEMA 5-15 plug
PR205740R	173L (6.1 cu. ft.)	2 supplied/4 max	520 x 520 x 700mm (20.5 x 20.5 x 28in.)	622 x 610 x 876mm (24.5 x 24 x 34.5in.)	± 0.6/1.0 °C*	-10° to +60 °C	230V 50Hz (5.8A), NEMA 6-15P plug
PR205740RCN	173L (6.1 cu. ft.)	2 supplied/4 max	520 x 520 x 700mm (20.5 x 20.5 x 28in.)	622 x 610 x 876mm (24.5 x 24 x 34.5in.)	± 0.6/1.0 °C*	-10° to +60 °C	230V 50Hz (5.8A), China plug
PR505755R	566L (20.0 cu. ft.)	4 supplied/6 max	508 x 673 x 1448mm (20 x 26.5 x 57in.)	787 x 864 x 1956mm (31 x 34 x 77in.)	± 0.5/0.9 °C**	-10° to +50 °C	120V, 60Hz (6.2A), NEMA 5-15P plug
PR505750R	566L (20.0 cu. ft.)	4 supplied/6 max	508 x 673 x 1448mm (20 x 26.5 x 57in.)	787 x 864 x 1956mm (31 x 34 x 77in.)	± 0.5/0.9 °C**	-10° to +50 °C	230V, 50/60Hz (3.1A), NEMA 6-15P plug
PR505750RCN	566L (20.0 cu. ft.)	4 supplied/6 max	508 x 673 x 1448mm (20 x 26.5 x 57in.)	787 x 864 x 1956mm (31 x 34 x 77in.)	± 0.5/0.9 °C**	-10° to +50 °C	230V, 50/60Hz (3.1A), China plug
Plant growth models with light at 20 °C							
PR505755L	504L (17.8 cu. ft.)	4 supplied/6 max	508 x 673 x 1448mm (20 x 26.5 x 57in.)	787 x 864 x 1956mm (31 x 34 x 77in.)	± 1.8 °C*** (0.9 °C w/o light)	-10° to +50 °C +10° to +50 °C***	120V, 60Hz (6.8A), NEMA 5-15P plug
PR505750L	504L (17.8 cu. ft.)	4 supplied/6 max	508 x 673 x 1448mm (20 x 26.5 x 57in.)	787 x 864 x 1956mm (31 x 34 x 77in.)	± 1.8 °C*** (0.9 °C w/o light)	-10° to +50 °C +10° to +50 °C***	230V, 60Hz (3.4A), NEMA 6-15P plug
* Performance values are based on 10 point measurements ** Performance values are based on 27 point measurements (DIN 12880) *** Lights switched on							
Additional shelving options							
Cat. No.	Description	Dimensions					
107384	52 x 44cm (20.5 x 17.5in)	Shelf for 173L units					
GT3185275	64 x 42cm (25.3 x 16.6in)	Shelf for 566L / 504L unit					

thermoscientific.com/incubators

© 2015 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

Australia +61 39757 4300
Austria +43 1 801 40 0
Belgium +32 53 73 42 41
China +800 810 5118 or
 +400 650 5118
France +33 2 2803 2180
Germany national toll free 0800 1 536 376
Germany international +49 6184 90 6000

India toll free 1800 22 8374
India +91 22 6716 2200
Italy +39 02 95059 552
Japan +81 3 5826 1616
Netherlands +31 76 579 55 55
New Zealand +64 9 980 6700
Nordic/Baltic/CIS countries
 +358 10 329 2200

Russia +7 812 703 42 15
Spain/Portugal +34 93 223 09 18
Switzerland +41 44 454 12 22
UK/Ireland +44 870 609 9203
USA/Canada +1 866 984 3766

Other Asian countries +852 2885 4613
Countries not listed +49 6184 90 6000

Thermo
 SCIENTIFIC
 A Thermo Fisher Scientific Brand