

Nalgene™ PMP Griffin Low-Form Plastic Beakers



Thermo Scientific™ Related applications: [General Plasticware](#)

Continuously use Thermo Scientific™ Nalgene™ PMP Griffin Low-Form Beakers at temperatures of 150°C with intermittent service to 175°C. These polymethylpentene beakers have the transparency of glass, excellent chemical resistance and heat tolerance. All sizes of beakers have easy to read, silk-screened graduations.

Product Size	Each
Certifications/Compliance	Meets ISO/DIN 7056 International Standards for Laboratory Plasticware Beakers
Description	Beaker Griffin Low-form PMP 4000mL
Capacity (Metric)	4000mL
Material	PMP (Polymethylpentene)
Quantity	1/Pk.; 4/Cs.
Type	Beaker

Description

- Transparent PMP material allows for a clear view of beaker contents
- No-drip, single-spout design provides precision pouring control
- With ribs for easy stacking
- Silk screened with graduations, size code, resin code, catalog number, max. temperature and "No Flame" symbol for easy identification and safe use
- Autoclavable/Graduated/Transparent
- Meets ISO/DIN 7056 International Standards for Laboratory Plasticware Accuracy

Warranty: 90 days. For warranty terms, please contact technicalsupport@thermofisher.com.

Disclaimer to internal research use restriction: Any restrictions on the purchaser to utilize the product(s) for internal research purposes only does not apply to the product(s) on the web pages associated with this statement.