

Visible SEDIMENT TEST CARD LLC

ORIGINATORS AND MANUFACTURERS
SEDIMENT, BLUE AND SCORCH PARTICLE TEST CARDS

Phuc Huynh, owner
2771 104th St., Suite V
Urbandale, IA 50322
P.O. Box 42455
Urbandale, IA 50323
USA

Telephone (515) 270-3854 or **800 275-6723**
From outside USA +01.515.270.3854
Fax: (515) 276-6593
E-mail: contact@visible-sediment.com
www.visible-sediment.com

Customer:

Type: Dry Laid, Chembond Solid Color Nonwoven

Description: "CONTEXT" # T-1313-1210 WHITE

Fiber Content: 100% 1.5D Rayon

Binder Content: 100% Acrylic Latex

Physical Properties:

	<u>Min.</u>	<u>STD.</u>	<u>Max.</u>
Basis Weight (oz./sq.yd.):	2.48	2.75	3.03
Thickness (Mils):	17.0	19.0	21.0
Tensile Strength (lb./in.) MD dry:	19.8	22.0	-
[cut strip method] CD dry:	11.0	12.5	-
MD wet:	6.0	7.0	-
CD wet:	3.0	3.5	-
Burst Strength (lbs./sq.in.) Dry:	32.0	36.0	-
[Mullen Tester] Wet:	21.0	24.0	-
Absorbency Rate (seconds) [in water]	-	5.0	10.0
Hand:		Stiff	
Air Perm (cfm/sq ft):	135	185	235

NOTE: Wet tensile test tested in water.