

# IFC200

## USB DATA LOGGER INTERFACE



### Features

- Compatible With Most MadgeTech Data Loggers
- "Plug and Play" - No Driver Installation Required
- Blue, Green and Red LED Indicators
- Reduced noise with longer sensor leads

MadgeTech's IFC200 interface cable communicates between stand alone data loggers and the MadgeTech software. Through this interface, loggers can be started, stopped or downloaded.



The IFC200 has been redesigned, and is now "plug and play". It can be directly connected to a computer without installing any drivers. The improved IFC200 can now operate at up to 500 Volts RMS relative to the computer's earth ground when attached.

The IFC200 is equipped with communication LE device status. The blue light illuminates when the device is plugged in and successfully recognized by Windows. The red light flashes when data is sent, and the green light flashes when data is received.



## IFC200 SPECIFICATIONS\*

**Operating Environment:** -20°C to +50°C  
(-4°F to +122°F)

**Materials:** Polycarbonate Enclosure

**Dimensions:** Enclosure: 1.9" x 0.69" x 0.32  
(48.4mm x 17.5mm x 8.1mm)  
Cable: 6' included  
May be used with any shielded 3.5mm stereo cable up to 100'

**LEDS:** Blue and Red/Green

Blue: Illuminates when the device is plugged in and successfully recognised by Windows.

**LED Functions:** Red: Flashes when data is sent.

Green: Flashes when data is received.

\*SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. SPECIFIC WARRANTY REMEDY LIMITATIONS APPLY. CALL 1-603-456-2011 OR GO TO [WWW.MADGETECH.COM](http://WWW.MADGETECH.COM) FOR DETAILS.

## ORDERING INFORMATION

MODEL	DESCRIPTION
IFC200	USB Data Logger Interface

For Quantity Discounts call 603-456-2011 or email [sales@madgetech.com](mailto:sales@madgetech.com)

ASK ABOUT  
OUR OTHER  
DATA  
LOGGERS

Temperature  
Humidity  
Pressure  
pH  
Level  
Shock  
LCD Display  
Pulse/Event/State  
Current  
Voltage  
Wireless  
Intrinsically Safe  
Spectral Vibration  
Motion