



Lift™ III

PRODUCT DESCRIPTION

Lift™ III is a low alkaline foaming cleaner formulated with a special blend of solvents for manual or foam cleaning of floors and walls or maintenance areas.

BENEFITS

Promotes Quality Assurance

- ▲ Unique formula enables its use on a broad range of environmental surfaces, including tile, block, concrete, painted surfaces and most metals, including aluminum, black iron and stainless steel.
- ▲ Optimum blend of surfactants and water soluble solvents provides rapid penetration of tough grease and oil-based soils.
- ▲ Rinses freely from surfaces.

Promotes Worker Safety

- ▲ Complete, liquid formula eliminates need for potentially hazardous practice of mixing several products.
- ▲ Effective spray or foam cleaning helps minimize worker exposure to concentrated product.
- ▲ Mildly alkaline, yet provides high level of soil penetration and removal, eliminating the need for scrubbing.
- ▲ Leaves no sticky or slippery residues.

Lift™ III

PROPERTIES	Form	liquid	pH 2% solution	10.8
	Color	pink	Alkalinity:	
	Odor	solvent	Active as Na ₂ O	0.8%
	Foam	high	Total as Na ₂ O	1.6%
	Spec. Grav. @ 68°F (20°C)	1.060		
	Pounds per gallon	8.90 (4.04 kg)		

Formula ingredients contain not more than 0.2% phosphorus, 0.2 g per gallon of average recommended use concentration.

DIRECTIONS FOR USE Lift III may be used for foam, spray or manual cleaning.
Concentrations:

Foam cleaning: 3-6 oz Lift III per gallon water (23.4-46.8 mL/L)
Manual cleaning: 1/2-2 oz Lift III per gallon water (3.9-15.6 mL/L)
Spray cleaning: 1-3 oz Lift III per gallon water (7.8-23.4 mL/L)

Consult your Ecolab Representative for specific use instructions and recommended dispensing equipment.

For cautionary and first aid information, consult the Material Safety Data Sheet (MSDS) or product label.

STATEMENT OF ASSURANCE This product is effective under the intended conditions of use as outlined on the product label or specified in a Sanitation Standard Operating Procedure (SSOP). This product will not adulterate food product provided that before using it, food products and packaging materials are removed from the room or carefully protected and after using these compounds, surfaces are thoroughly rinsed with potable water.

A Letter of Guaranty as indicated in USDA's Sanitation Performance Guideline is available from your Ecolab representative.

ECOLAB SUSTAINABILITY POLICY We have a commitment to our customers to provide effective programs that help protect the health and safety of their customers and employees. We will sell products or services that maximize performance, limit total environmental impact, and are safe as our customers commonly use them. We will inform our customers of the environmental impacts of our products or services, and of their correct use.

Distributed by:
NELSON JAMESON
INC.
800-826-8302 nelsonjameson.com

