



Distributed by:
NELSON JAMESON
INC.
800-826-8302 nelsonjameson.com

Customer Specification Sol-Vex #37-175

PRODUCT NOMENCLATURE

Manufacturing Glove Code: **#37-175**
Manufacturing Glove Name: **Sol-Vex**
Marketing Glove ASPN Code(s): **(6)-117272 (7)-117273 (8)-117274 (9)-117275 (10)-117276 (11)-117277**

PRODUCT DESCRIPTION

Product Classification:	Chemical Resistant (Unsupported)	Lining:	Cotton Flock
Exterior Color:	Green		
Former Pattern Style:	Sandpatch	Exterior Finish:	Chlorinated
Coating Composition:	Nitrile	Cuff Finish:	Straight (unpinked)
Available Sizes:	6, 7, 8, 9, 10 and 11	Printing:	Inkjet Black
Packaging:	12 Pairs per inner bag	Length:	12.75 in. (324 mm) Minimum
	12 Inner bags per case (144 Pairs)		

OUTSTANDING CHARACTERISTICS & APPLICATIONS

- ◆ Provides excellent snag, puncture, abrasion and cut resistance.
- ◆ Outstanding resistance to a wide range of chemicals, including aromatic solvents, petroleum solvents and animal fats.
- ◆ **APPLICATIONS:** *Chemical Processing, Oil Refining, Petrochemicals, Food Processing (red meat, poultry, vegetables, fruit, dairy and canning), Aerospace and Automotive Degreasing, Automotive Painting and Assembly, Machining Operations, Metal Fabrication, Graphic Arts, Furniture Manufacturing, Electronics (semiconductors & circuit boards)*

REGULATORY COMPLIANCES

- ◆ Complies with FDA regulation 21 CFR 177.2600 for food contact applications.

TYPICAL PERFORMANCE VALUES

◆ Thickness	15 ± 2 mils (0.28 ± 0.05 mm)	ASTM D 412
◆ Tensile Strength	> 3000 psi (> 20.7 Mpa)	ASTM D 412
◆ 300% Modulus	2500 psi (17.2 Mpa) Maximum	ASTM D 412
◆ Elongation @ Break	> 400%	ASTM D 412
◆ Abrasion Resistance	Performance Level 4	EN 388, ANSI/ISEA 105-2000
◆ Cut Resistance	Performance Level 0	ANSI/ISEA 105-2000
◆ Cut Resistance	Performance Level 1	EN 388
◆ Puncture Resistance	Performance Level 2	EN 388, ANSI/ISEA 105-2000
◆ Chemical Resistance	Varies by challenge chemical	ASTM F 739, ANSI/ISEA 105-2000

DEFECTS

DEFINITIONS: **Major Defects** are imperfections which *may result* in the failure of the glove to perform it's intended purpose, cause user discomfort or be cosmetically objectionable. **(AQL- 1.0%)**
Minor Defects may cause user discomfort or be cosmetically objectionable. **(AQL- 2.5%)**
MAJOR DEFECTS: **Holes/Splits/Tears/Thin Spots/No Flock/Porosity**
MINOR DEFECTS: **Blisters/Runs/Lumps/Webs/Stains/Creases/Poor Pinking/Insufficient Flock/Ink Smear**

GENERAL INFORMATION

SHELF LIFE: Five (5) years in cool, covered conditions. Extended exposure to direct sunlight or excessive heat will reduce shelf life and result in fading, discoloration and cracking.
NOTE: *This product contains NO natural rubber latex. This product has no silicone-containing components.*

Originator: Paul McMorrow	Date: 02/06/01	Revision #: 1 (added ANSI/ISEA Performance Levels) 2 (added "no silicone" to " NOTE " section)
Revised By: Paul McMorrow	Date: 05/25/04	
Paul McMorrow	06/15/09	

NEITHER THIS NOR ANY STATEMENT MADE BY OR ON BEHALF OF ANSELL HEREIN IS A WARRANTY THAT ANY PRODUCT IS FIT FOR A PARTICULAR PURPOSE, AND ANSELL SHALL NOT BE LIABLE TO ANYONE WITH RESPECT TO THIS INFORMATION.

