

SHOWA 708

Ambidextrous blue lightweight glove with superior grip, 100% nitrile, latex- and powder-free.

[FEATURES

- Food-safe organic formulation and blue colour
- 100% nitrile, latex-free and unflocked
- Beaded cuff
- Liquid-proof
- 300mm long and 0.23mm thick
- Strong chemical resistance EN ISO 374-1 : JKOPT

[BENEFITS

- Superior fish scale grip inside and out for safer, extended handling in messy wet and oily conditions
- Fingertip and inner-thumb texturing provides user with excellent grip and tactility to prevent accidents and unintended damage while reducing hand fatigue
- Highest dexterity level (EN420 Level 5) makes the glove suitable for use with all food categories in situations where there is short term, repeated contact
- Unflocked to prevent the risk of food contamination
- Thicker nitrile compound provides exceptional resistance to chemicals
- Webbing in the glove from the grip pattern provides extra strength against tears

[INDUSTRY



Agriculture



Chemical



Food



Janitorial



Mechanical

[IDEAL APPLICATIONS

- Handling plants and vegetables
- Light chemical handling in agriculture, horticulture
- Chemical spray and treatment
- Painting & spray workshops
- Food packing and handling
- Sanitation and dishwashing
- Light assembly of oil-coated pieces



MATERIAL

- Unsupported


COATING

- chemical resistant
- Nitrile
- Water resistant

GRIP

- Embossed

STANDARDS



SHOWA 708



PACKAGING

- 24 Pair per polybag
- 10 Dispenser per case
- 240 Pair per case



SIZES

- 7/S
- 8/M
- 9/L
- 10/XL
- 11/XXL
- 12/XXXL



COLOUR

- Blue



THICKNESS

- 9 mil



[YOU MIGHT ALSO BE INTERESTED IN

SHOWA 707D



MATERIAL
Single use
COATING
chemical
resistant

SHOWA 707HVO



MATERIAL
Unsupported
COATING
Biodegradable

SHOWA 6112PF



MATERIAL
Single use
COATING
Biodegradable

SHOWA 9700PF



MATERIAL
Single use
COATING
Nitrile

[USER INSTRUCTIONS

Protection against mechanical risks, with electrostatic properties. Do not use where there are chemical, electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light. All clothing and shoes worn with the glove with electrostatic dissipation properties must also be designed taking the electrostatic risk into account.

[DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

Distributed by:

NELSON JAMESON

INC.

800-826-8302 nelsonjameson.com