

P2A

Technical Specifications



SPECIFICATIONS	
SHELL MATERIAL	Injection molded fiberglass compound
SUSPENSION TYPES AVAILABLE	Ratchet, Swingstrap
SUSPENSION POINTS	8
ACCESSORY SLOTS	No
RAIN THROUGH	No
AVAILABLE SHELL COLORS	White (01), Yellow (02), Green (04), Grey (09), Black (11), Red (15), Hi-Viz Strong Orange (46), Blue (71)
STANDARDS PASSED	ANSI Z89.1-2014 Type I Class G, CSA Z94.1-2015 Type I Class G or C
OPERATIONAL LOW TEMP (-30°C)	No (High heat protection up to 370°F)
REVERSE DOWNING	Yes
CUSTOM IMPRINTS AVAILABLE	Yes
DIELECTRIC	Class C or G
PACKAGING	20 per case
UNIT WEIGHT	15.7 oz
IND. BOX/BAG DIMENSIONS	12 in x 8 in x 7 in
IND. BOX/BAG WEIGHT	15.7 oz
MASTER CASE DIMENSIONS	19 in x 23 in x 23 in
MASTER CASE WEIGHT	23 lb
COUNTRY OF ORIGIN	Mexico
HARMONIZATION CODE	6506.10.3075

WARNING: This reference provides only an overview of the products shown. It does not provide important product warnings and instructions. Honeywell Safety Products recommends that all users of its products undergo thorough training and that all warnings and instructions provided with the products be thoroughly read and understood prior to product use. A complete and thorough hazard assessment must be conducted to properly identify the appropriate personal protective equipment to be used in a particular work environment. **FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS AND TO PROPERLY PERFORM A HAZARD ASSESSMENT MAY RESULT IN SERIOUS PERSONAL INJURY, ILLNESS OR DEATH.**

Distributed by:

NELSON JAMESON
INC.

800-826-8302 nelsonjameson.com