



Product Family
XTP™ PVC Footwear

- XTP™ is engineered with chemical resistance formulation
- Seamless, 3-stage, PVC injection molded construction is 100% waterproof
- TDT outsole compounds are formulated for long wear reducing cost of inventory and slip resistance
- Engineered outsole has a dual compound
- Steel toe protection



Product Numbers & Ordering Information

	Product Numbers	Details
	75108	Servus®, XTP®, PVC, TDT Technology Footwear, Plain toe Boot – XTP® – PVC – 15 in (38.1 cm) – Black/Red/Gray – Plain toe – extended ribbed steel shank – removable and washable ergonomic insoles – Men's whole sizes: 3 - 15
	75109	Servus®, XTP®, PVC, TDT Technology Footwear, Steel toe Boot – XTP® – PVC – 15 in (38.1 cm) – Black/Yellow/Gray – "Safe-Toe" steel toe – extended ribbed steel shank – removable and washable ergonomic insoles – Men's whole sizes: 3 - 15

Packaging Information

1 pair per bag, 6 pair per case

Hazardous Materials

NA

Overview

Key Features

- XTP™ is engineered with reinforced construction and chemical resistance formulation to provide superior protection in harsh environments
- Seamless, 3-stage, PVC injection molded construction is 100% waterproof to keep feet comfortable and dry
- TDT outsole compounds are formulated for long wear and slip resistance, reducing the cost of inventory and injury
- Engineered outsole has a dual compound, durable exterior for abrasion and harsh conditions and a softer interior for comfort and excellent traction to prevent slips and falls
- Removable FOOT FORM contour cushion insoles provides support for comfort and wicks away moisture to keep workers' feet dry
- Higher, wider, kick-off lugs for easy on/off convenience

Recommended Industries/Use

- Agriculture
- Chemical
- Government
- Military
- Municipal Services
- Oil and Gas
- Utilities
- Nuclear

Hazards

- Abrasion
- Chemical
- Impact
- Slip
- Splash

Regulations

- American Society of Testing and Materials - ASTM F2413-11
- ANSI Z41-1991 - OSHA 1910.136 states; The employer shall ensure that each affected employee uses protective footwear when working in areas where there is a danger of foot injuries due to falling or rolling objects, or objects piercing the sole, and where such employee's feet are exposed to electrical hazards. For more information go to www.osha.gov.
- Canadian Standards Association - CAN/CSA Z195-09

Historical Brand

Norcross Safety Products

Warranty Information

Each new Product manufactured and/or sold by NSP is warranted to be free from defects in material and/or workmanship. NSP's responsibility is limited to, at its option repairing or replacing any instrument or part thereof, or issuing a credit, for a period of one year after shipment. NSP's warranty sets forth the limit of NSP's responsibility. ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS, ARE EXCLUDED

Specifications

Construction

- Cut and sewn

Construction

- Injection molded

Height

- 15 inch (38.1 cm)

Height

- NA

Insole

- Foot Form

Insole

- NA

Insulated

- NA

Insulated

- No

Material

- Acrylic/cotton

Material

- PVC

Metatarsal Protection

- NA

Metatarsal Protection

- None

Sizes

- Men's sizes 3 - 15

Steel Midsole Protection

- NA

Steel Midsole Protection

- None

Steel Toe Protection

- NA

Steel Toe Protection

- Style # 75109 has steel toe protection

Tread

- NA

Tread

- TDT outsole

Waterproof

- No

Waterproof

- Yes

© Honeywell International Inc.

Distributed by:
NELSON JAMESON
INC.
800-826-8302 nelsonjameson.com