



## Ultra-spec® 2001 OTG

Lens overall width	158 mm (6.2" nominal)
Lens material	Polycarbonate
Lens coating	Ultra-dura®, Uvextreme® AF
Lens thickness	2.0 mm (.08 in) min
Available lens tints	Clear, Gray
Replacement lenses available (yes/no)	No
Rx capable	Over-the-glass design fits over most Rx eyewear
Temple material	Nylon
Temple length	110 mm (4.5")
Temple set-back	100 mm (4.0")
Temple style	Duoflex® cushioned
Spectacle weight	44 grams (1.5 oz.) approx.
Frame material	Not applicable
Available temple colors	Black/Black
Dielectric frame (yes/no)	Yes
Standards passed	ANSI Z87+, CSA Z94.3
Packaging	Ind. box, 10/stocker, 200/case

**WARNING:** This reference manual provides only an overview of the products shown. It does not provide important product warnings and instructions. Sperian Protection recommends all users of its products undergo thorough training and that all warnings and instructions provided with the products be thoroughly read and understood prior to use. It is necessary to assess hazards in the work environment and to match the appropriate personal protective equipment to particular hazards that may exist. At a minimum, a complete and thorough hazard assessment must be conducted to properly identify the appropriate personal protective equipment to be used in a particular work environment. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS AND TO PROPERLY PERFORM A HAZARD ASSESSMENT MAY RESULT IN SERIOUS PERSONAL INJURY, ILLNESS OR DEATH.