

SAFETY DATA SHEET

HYDRI-SAN NO. 468
Product ID: FP046801
Revised: 01-02-2024
Replaces: 09-04-2013

1. IDENTIFICATION

Product Identifier Used HYDRI-SAN NO. 468
on the Label:

Other Identifiers: B-98054A
Product ID: MIXTURE
Recommended Use: No data available.
Restrictions on Use: No data available.

Hydrite Chemical Co.
17385 Golf Parkway
Brookfield, WI 53045
(262) 792-1450

EMERGENCY RESPONSE NUMBERS:
24 Hour Emergency #: (414) 277-1311
CHEMTREC Emergency #: (800) 424-9300

2. HAZARD(S) IDENTIFICATION

GHS Classification(s): Substance or mixture corrosive to metals Category 1
Skin Corrosion/Irritation Category 1B
Serious Eye Damage/Eye Irritation Category 1
Carcinogenicity Category 1A
Acute Toxicity - Inhalation Dust / Mist Category 4
Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3

GHS Label Elements:

GHS Hazard Symbols:



Signal Word: Danger

Hazard Statements: May be corrosive to metals.
Causes severe skin burns and eye damage.
Harmful if inhaled.
May cause respiratory irritation.
May cause cancer.

Precautionary Statements:

Prevention: Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep only in original container.
Do not breathe dust/fume/gas/mist/vapours/spray.
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.

Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a POISON CENTER or doctor/physician.
Specific treatment (see First Aid on SDS or on this label).
Wash contaminated clothing before reuse.
Absorb spillage to prevent material damage.

Storage: Store in a well-ventilated place. Keep container tightly closed.
Store in a secure manner.
Store in corrosive resistant container with a resistant inner liner.

Disposal: Dispose of in accordance with local, regional and international regulations.

Hazards not otherwise classified: Excessive exposure may cause central nervous system effects. May react with certain metals to form explosive/flammable hydrogen gas.
May react violently with water.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances/Mixtures:

<u>Chemical or Common Name/Synonyms</u>	<u>CAS Number</u>	<u>% by Wt.</u>
Phosphoric Acid	7664-38-2	40 - 50 %
*C(10-16)-Alkylbenzenesulfonic Acid	68584-22-5	10 - 20 %
Sulfuric Acid	7664-93-9	< 1.0 %

Note: * Alternate CAS#: 27176-87-0, 85536-14-7

Note: Any chemical identity and/or exact percentage not expressly stated is being withheld as a trade secret or is due to batch variation.

4. FIRST-AID MEASURES

Description of Necessary Measures:

Eye Contact: If in eyes: Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. Tilt head to avoid contaminating unaffected eye. Get immediate medical attention. Remove contact lens if easy to do.

Skin Contact: If on skin: Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately. Do not reuse clothing and shoes until cleaned. Do not apply oils or ointments unless ordered by the physician.

Inhalation: If inhaled: Remove to fresh air. If breathing is difficult, administer oxygen. If not breathing, give artificial respiration, preferably mouth-to-mouth. GET MEDICAL ATTENTION IMMEDIATELY. DO NOT use mouth-to-mouth method if victim ingested or inhaled the substance; induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Ingestion: If swallowed: If fully conscious, drink a quart of water. DO NOT induce vomiting. CALL A PHYSICIAN IMMEDIATELY. If unconscious or in convulsions, take immediately to a hospital or a physician. NEVER induce vomiting or give anything by mouth to an unconscious victim. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs.

Most Important Symptoms/Effects, Acute and Delayed:

Eye Contact: CORROSIVE-Causes severe irritation and burns. May cause: ulcerations. conjunctivitis. permanent eye damage. blindness.

Skin Contact: CORROSIVE-Causes severe irritation and burns. Contact may cause: dermatitis (inflammation of the skin). ulceration. severe burns. permanent skin damage.

Skin Absorption: No absorption hazard expected under normal use.

Inhalation: CORROSIVE-Causes severe irritation and burns. Vapors or mists may irritate or burn: respiratory tract. nose. mouth. throat. May cause: persistent coughing. pulmonary edema. chemical pneumonitis. permanent damage. Effects may be delayed. Vapors or mists may cause: sore throat. shortness of breath.

Ingestion: CORROSIVE-Causes severe irritation and burns. May irritate or burn: mouth. throat. stomach. esophagus. May cause: abdominal pain. chest pain. nausea. vomiting. diarrhea. seizures. hemorrhaging. permanent damage. Aspiration into the lungs may occur during ingestion or vomiting, resulting in severe pulmonary injury. May be fatal if swallowed. Large amounts may cause: central nervous system effects.

Indication of Immediate Medical Attention and Special Treatment Needed: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: Not flammable or combustible. For fires in area use appropriate media. For example: Water spray. Dry chemical. Carbon dioxide. Foam.

Specific Hazards Arising from the Chemical:

Fire and Explosion Hazards: Product may react with some metals (ex.: Aluminum, Zinc, Tin, etc.) to release flammable hydrogen gas.

Hazardous Combustion Products: Phosphorous oxides. Phosphine. Toxic vapors. Corrosive vapors. Carbon dioxide. Carbon monoxide. Aldehydes. Ketones. Sulfur dioxide. Sulfur oxides. Sulfuric acid.

Special Protective Equipment and Precautions for Fire-Fighters: Evacuate area of unprotected personnel. Wear protective clothing including NIOSH-approved self-contained breathing apparatus. Remain upwind of fire to avoid hazardous vapors and decomposition products. Use water spray to cool fire-exposed containers and disperse vapors. Product generates heat upon addition of water, with possible spattering. Run-off from fire control may cause pollution.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, Emergency Procedures: CORROSIVE MATERIAL. Evacuate unprotected personnel from area. Maintain adequate ventilation. Follow personal protective equipment recommendations found in Section 8. Never exceed any occupational exposure limit.

Methods and Materials for Containment and Clean Up: Contain spill, place into drums for proper disposal. Soak up residue with inert absorbent material. Place in non-leaking containers for immediate disposal. Flush remaining area with water and neutralize with Soda Ash, Lime or Limestone and dispose of properly. Adequate ventilation is required if soda ash is used, because of the consequent release of carbon dioxide gas. Avoid direct discharge to sewers and surface waters. Notify authorities if entry occurs. CAUTION: Spilled material may be slippery.

7. HANDLING AND STORAGE

Precautions for Safe Handling: Avoid contact with eyes, skin, and clothing. Use with adequate ventilation. Do not swallow. Avoid breathing vapors, mists, or dust. Do not eat, drink, or smoke in work area. Wash thoroughly after handling. Empty containers retain product residue (vapor, dust, or liquid) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other source of ignition. They may explode and cause injury or death. CORROSIVE MATERIAL. Contact with

water may cause violent reaction with evolution of heat. To dilute: Add product slowly to lukewarm water; not water to product. Mixing with strong bases can cause high heat of reaction and generate steam.

Conditions for Safe Storage, Including any Incompatibilities: CORROSIVE MATERIAL. Store in a cool, well ventilated area, out of direct sunlight. Store in a dry location away from heat. Keep away from incompatible materials. Keep containers tightly closed. Do not store in unlabeled or mislabeled containers. Do not freeze. May react with certain metals to form explosive/flammable hydrogen gas.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

OSHA Exposure Guidelines:

Component	Limits
Phosphoric Acid	1 mg/m3 TWA
Sulfuric Acid	1 mg/m3 TWA

ACGIH Exposure Guidelines:

Component	Limits
Phosphoric Acid	1 mg/m3 TWA; 3 mg/m3 STEL
Sulfuric Acid	0.2 mg/m3 TWA (thoracic particulate matter)

Appropriate Engineering Controls: General room ventilation and local exhaust are required. Maintain adequate ventilation. Do not use in closed or confined spaces. Avoid creating dust or mist. Keep levels below exposure limits. To determine exposure levels, monitoring should be performed regularly.

Individual Protection Measures:

Eye/Face Protection: Wear chemical safety goggles and a full face shield while handling this product. Do not wear contact lenses.

Skin Protection: Prevent contact with this product. Wear gloves and protective clothing depending on condition of use. Protective gloves: Impervious. Chemical-resistant. Acid-proof.

Respiratory Protection: Respiratory protection must be worn if ventilation does not eliminate symptoms or keep levels below recommended exposure limits. If exposure limits are exceeded, wear: NIOSH-Approved respirator. DO NOT exceed limits established by the respirator manufacturer. All respiratory protection programs must comply with OSHA 29 CFR 1910.134 and ANSI Z88.2 requirements and must be followed whenever workplace conditions require a respirator's use.

Other Protective Equipment: Eye-wash station. Safety shower. Rubber apron. Chemical safety shoes. Rubber boots. Protective clothing.

General Hygiene Conditions: Wash with soap and water before meal times and at the end of each work shift. Good manufacturing practices require gross amounts of any chemical be removed from skin as soon as practical, especially before eating or smoking. Food, beverages, and tobacco products should not be carried, stored or consumed where this material is in use. Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid.

Color: Clear. Light yellow / brown.

Odor: No odor.

Odor Threshold: N.D.

pH: 1 (as is)

Freezing Point (deg. F): N.D.

Melting Point (deg. F): N.D.

Initial Boiling Point or Boiling Range: N.D.

Flash Point: > 201 °F

Flash Point Method: Estimated.

Evaporation Rate (nBuAc = 1): N.D.

Flammability (solid, gas): N.D.

Lower Explosion Limit: N.D.
Upper Explosion Limit: N.D.
Vapor Pressure (mm Hg): N.D.
Vapor Density (air=1): N.D.
Specific Gravity or Relative Density: 1.3150 @ 25 C
Solubility in Water: Soluble
Partition Coefficient (n-octanol/water): N.D.
Auto-ignition Temperature: No Data
Decomposition Temperature: N.D.
Viscosity: N.D.
% Volatile (wt%): N.D.
VOC (wt%): N.D.
VOC (lbs/gal): N.D.
Fire Point: N.D.

10. STABILITY AND REACTIVITY

Reactivity: No data available.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur under normal conditions. May react with certain metals to form explosive/flammable hydrogen gas. Mixing with strong bases can cause high heat of reaction and generate steam. Phosphoric acid forms flammable gases with sulfides, mercaptans, cyanides and aldehydes. Phosphoric acid forms toxic fumes with cyanides, sulfides, fluorides, organic peroxides, and halogenated organics. Phosphoric acid mixtures with nitromethane are explosive.

Conditions to Avoid (e.g., static discharge, shock, or vibration): Contact with water may cause violent reaction with evolution of heat. To dilute: Add product slowly to lukewarm water; not water to product. Avoid high temperatures.

Incompatible Materials: Strong oxidizing agents. Strong alkalis. Strong bases. Metals. Strong reducing agents. Sulfides. Sulfites. Bases. Fluorine. Sulfur trioxide. Phosphorous pentoxide. Sodium tetrahydroborate. Aldehydes. Amines. Amides. Alcohols. Azo-compounds. Carbamates. Esters. Caustics. Phenols. Cresols. Ketones. Organophosphates. Epoxides. Explosives. Combustible materials. Unsaturated halides. Organic peroxides. Mercaptans. Cyanides. Nitromethane. Glycols. Fluorides. Halogenated organics. Sulfur. Aluminum. Copper. Mild steel. Brass. Bronze. Steel.

Hazardous Decomposition Products: Phosphorous oxides. Phosphine. Reactions with other materials may liberate toxic and/or explosive gases. Carbon dioxide. Carbon monoxide. Aldehydes. Ketones. Toxic vapors. Alcohols. Ethers. Organic acids. Sulfur dioxide. Sulfur oxides. Sulfuric acid.

11. TOXICOLOGICAL INFORMATION

Routes of Exposure: Eyes. Skin. Inhalation. Ingestion.

Symptoms/Effects: Acute, Delayed and Chronic:

Eye Contact: CORROSIVE-Causes severe irritation and burns. May cause: ulcerations. conjunctivitis. permanent eye damage. blindness.

Skin Contact: CORROSIVE-Causes severe irritation and burns. Contact may cause: dermatitis (inflammation of the skin). ulceration. severe burns. permanent skin damage.

Skin Absorption: No absorption hazard expected under normal use.

Inhalation: CORROSIVE-Causes severe irritation and burns. Vapors or mists may irritate or burn: respiratory tract. nose. mouth. throat. May cause: persistent coughing. pulmonary edema. chemical pneumonitis. permanent damage. Effects may be delayed. Vapors or mists may cause: sore throat. shortness of breath.

Ingestion: CORROSIVE-Causes severe irritation and burns. May irritate or burn: mouth. throat. stomach. esophagus. May cause: abdominal pain. chest pain. nausea. vomiting. diarrhea. seizures. hemorrhaging. permanent damage. Aspiration into the lungs may occur during ingestion or vomiting, resulting in severe pulmonary injury. May be fatal if swallowed. Large amounts may cause: central nervous system effects.

Numerical Measures of Toxicity:

Component	Oral LD50	Dermal LD50	Inhalation LC50
Phosphoric Acid	Rat: 1530 mg/kg	Rabbit: 2740 mg/kg	1H Rat: > 850 mg/m3
*C(10-16)-	Rat: 1260 mg/kg	Rabbit: 631 - 1000 mg/kg	No Data
Alkylbenzenesulfonic Acid			
Sulfuric Acid	Rat: 2140 mg/kg	No Data	4H Rat: 0.4 mg/L

Acute Toxicity Estimates (ATE):

Oral: 2668 mg/kg
Dermal: 8028 mg/kg

Cancer Information:

This product contains 0.1% or more of the following chemicals listed by NTP, IARC or OSHA as known or possible carcinogens:
Sulfuric acid mist

Medical Conditions Aggravated by Exposure to Product: Eye disorders. Skin disorders. Impaired respiratory function. Kidney disorders. Respiratory system disorders.

Other: Sulfuric acid, per se, is not listed as a carcinogen by OSHA, the National Toxicology Program (NTP), the International Agency for Research on Cancer (IARC), or the ACGIH. IARC has concluded that there is sufficient evidence that occupational exposure to strong inorganic acid mists containing sulfuric acid is carcinogen to humans, resulting in an increased incidence of primary laryngeal cancers. The ACGIH lists strong inorganic acid mists containing sulfuric acid as a suspected human carcinogen (A2) and the NTP have classified inorganic acid mists containing sulfuric acid as a known human carcinogen. OSHA does not list sulfuric acid mist as a carcinogen.

12. ECOLOGICAL INFORMATION

Ecotoxicological Information: No data available.

Chemical Fate Information: No data available.

13. DISPOSAL CONSIDERATIONS

Hazardous Waste Number: D002

Disposal Method: Dispose of in a permitted hazardous waste management facility following all local, state and federal regulations. Since emptied containers retain product residue, follow label warnings even after container is emptied. DO NOT pressurize, cut, weld, solder, drill, grind or expose empty containers to heat, flame, sparks or other sources of ignition. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Disposal methods identified are for the product as sold. For proper disposal of used material, an assessment must be completed to determine the proper and permissible waste management options permitted under applicable rules, regulations and/or laws governing your location.

14. TRANSPORTATION INFORMATION

DOT (Department of Transportation):

Identification Number: UN1760
Proper Shipping Name: Corrosive Liquid, N.O.S. (Contains Dodecylbenzenesulfonic Acid, Phosphoric Acid)

Hazard class: 8
Packing Group: III
Label Required: CORROSIVE
Reportable Quantity (RQ): 5000# (Phosphoric Acid); 1000# (Dodecylbenzenesulfonic Acid); 1000# (Sulfuric Acid)

15. REGULATORY INFORMATION

TSCA Inventory Status: All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

SARA Title III Section 311/312 Category Hazards: Please see Section 2 of this SDS.

Regulated Components:	CAS	CERCLA	SARA	SARA	U.S.	WI	Prop
Component	Number	RQ	EHS	313	HAP	HAP	65
Phosphoric Acid	7664-38-2	Yes	No	No	No	Yes	No
*C(10-16)-Alkylbenzenesulfonic Acid	68584-22-5	Yes	No	No	No	No	No
Sulfuric Acid	7664-93-9	Yes	Yes	Yes	No	Yes	Yes

***Prop 65 - May Contain the Following Trace Components:**

This product can expose you to chemicals including (ethylene oxide, strong inorganic acid mists containing sulfuric acid) which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov. (Este producto puede exponerlo a sustancias químicas que incluyen (óxido de etileno, nieblas de ácido inorgánico fuerte que contienen ácido sulfúrico) que el estado de California reconoce como causantes de cáncer y defectos de nacimiento u otros daños reproductivos. Para obtener más información, visite www.P65Warnings.ca.gov.)

Note: * Sulfuric acid appears on the Section 313 List. However, the listing only applies to the aerosol forms of sulfuric acid.

FIFRA Information:

This chemical is a pesticide product registered by the Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets, and for workplace labels of non-pesticide chemicals.

Hazards to Humans and Domestic Animals

Danger: Corrosive. Causes irreversible eye damage or skin burns. Harmful if swallowed or absorbed through skin or inhaled. Do not get in eyes, on skin or on clothing. Avoid breathing spray mist. Wear goggles or face shield. Wear protective clothing and rubber gloves. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash clothing before reuse.

Environmental Hazards

Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or public waters unless this product is specifically identified and addressed in a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to the discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

16. OTHER INFORMATION

Hazard Rating System

Health: 3*

Flammability: 0

Reactivity: 0

* = Chronic Health Hazard

NFPA Rating System

Health: 3

HYDRI-SAN NO. 468
Product ID: FP046801

Flammability: 0
Reactivity: 0
Special Hazard: None

SDS Abbreviations

N.A. = Not Applicable

N.D. = Not Determined

HAP = Hazardous Air Pollutant

VOC = Volatile Organic Compound

C = Ceiling Limit

N.E./Not Estab. = Not Established

SDS Prepared by:

Reason for Revision: Changes made throughout the SDS.

Revised: 01-02-2024

Replaces: 09-04-2013

The data in this Safety Data Sheet relates to the specific material designated and does not relate to its use in combination with any other material or process. The data contained is believed to be correct. However, since conditions of use are outside our control it should not be taken as warranty or representation for which HYDRITE CHEMICAL CO. assumes legal responsibility. This information is provided solely for your consideration, investigation, and verification.