

CS30H Heavy Duty BOPP Box Sealing Tape

Product Description	<ul style="list-style-type: none">• BOPP film coated tape• General purpose packaging tape used for box sealing, splicing and other packaging applications.• Resistant to various chemicals and corrosion		
Applications	<ul style="list-style-type: none">• Holding and bundling application where moisture resistance is required• Protect labels• Single Strips closure of regular slotted containers (RSC’s) applied with a hand held dispenser		
Features/Benefits	<ul style="list-style-type: none">• Suitable for cold storage• High Tack• Portable/ Impact resistance• Water resistance• Controlled unwind		
Construction	Film	Biaxially oriented polypropylene film	
	Adhesive	Thermoplastic rubber	
	Color	Clear	
Physical Properties	Note: The following technical information and data should be considered representative or typical only.		
	Total Thickness	3.0 ± 0.04 mil	Test method: PSTC-133
	Adhesion to steel	80 oz./in	Test method: ASTM D-1000
	Temp. Resistance	-37°C to 54°C (35°F to 130°F)	Test method: PSTC-107
	Tensile Strength	46 lbs./in	Test method: PSTC-131
	Elongation at Break	140%	Test method: PSTC-131
Temperature Conditions	Application	32° F ~ 104° F (0° C ~ 40° C)	
	Operating	14° F ~ 122° F (-10° C ~ 50° C)	
	Storage	Recommended one-year shelf life from date of dispatch, if kept at moderate temperatures and humidity levels	

Note to Buyer/User: All statements, information, and recommendations herein are based on calculations and tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. The technical information and data obtained from tests are considered representative and should not be used for specification purposes recommended by PSTC. Before using, buyer/user shall determine suitability of the product for the product for its intended use and buyer/user assumes all risk and liability whatsoever in connection therewith. The seller limits its obligation to replacement, or, at its option, reimbursement of the purchase price of products shown to the seller's satisfaction to have been defective at the time the seller sold it.