

BEING Water Baths

BEING General Purpose Water Baths are ideal for maintaining temperature set points from ambient to 100°C over a long period of time. Different sizes and depths of the bath chamber are available to meet specific application needs.

Technical Advantage Performance and Features

- Temperature Range: Ambient +5° to 99°C.
- P.I.D. temperature controller.

Convenience

- Large LCD display screen and interface provides for user-friendly operation.
- Easy to set adjustable timer.
- Maintenance-free operation with easy to clean surface.
- Both heater and bath chamber are made of corrosion resistant stainless steel.
- No angle in bath chamber, easy to clean.
- The standard stainless steel bottom plate, helps prevents direct contact by accessories and tubes to heating element and sensors.
- Drain valve makes emptying of bath water fast and easy for cleaning and moving.

Safety

- Preset on/off function.
- Built-in power interruption protection function, automatic run after power interruption.
- Independent over temperature protection meets DIN 12880 International standard requirements.
- Temperature deviation alarm.
- Over current protection alarm.
- Independent over-temperature limit controller for added safety.



Model	BWB-5 (157-1046)	BWB-12 (157-1048)	BWB-22 (157-1050)
Capacity	5 L	10 L	20 L
Temperature Range	Ambient +5° to 99°C		
Temperature Fluctuation	±0.3°C		
Timer	1 to 5999-min	1 to 5999-min	1 to 5999-min
Internal Dimension (W x H x D)	11.0" x 5.9" x 5.1" (280 x 150 x 130 mm)	11.0" x 5.9" x 8.7" (280 x 150 x 220 mm)	19.3" x 5.9" x 11.8" (490 x 150 x 300 mm)
External Dimension (W x H x D)	13.6" x 13.4" x 7.9" (345 x 340 x 200 mm)	13.5" x 14.0" x 11.2" (345 x 355 x 285 mm)	21.4" x 14.0" x 13.5" (545 x 355 x 343 mm)
Net Weight	5 Kg	12 Kg	18 Kg
Electrical Requirement	AC120 V, 60 Hz		
Power Consumption	500 Watt	750 Watt	1450 Watt