

# Nasco SAMPLING

---

**Product Data Sheet**  
**Nasco Sludge Judge® Ultra (15' Long)**  
**B01386WA**

- **Material** – Clear plastic (Polycarbonate) tubing
- **Inner/Outer Dimensions** – .885 (+/- .005), 1.045 (+/- .005)
- **Construction** –
  - **Top Section with Rope** (B01387WA) – five-foot length, threaded nylon connector on one end, three-foot nylon rope on the top end, one-foot markings on the tube.
  - **Middle/Extension Section** (B01388WA) – five-foot length, threaded nylon connector on each end, one-foot markings on the tube.
    - Additional extension sections can be added to make the unit longer.
  - **Bottom Section** (B01389WA) – five-foot length, nylon float valve on one end, threaded nylon connector on the other, one-foot markings on the tube.
- **Capacity** – Holds approximately three ounces per foot.
- **Application** – As unit is lowered into the liquid, the float valve opens allowing material to enter; when bottom of tank is reached, unit is raised up with a slight tug to set the valve holding the material inside. Sludge level can be seen using the one-foot markers on the tube. Touch the tip of the float valve against a hard surface and the liquid will empty out through the bottom section.
- **Accessories** – A six-foot cleaning brush (B01291WA) made of galvanized steel wire and polyester bristles is available separately.

*Distributed by:*

**NELSON**  **JAMESON**  
INC.

800-826-8302 [nelsonjameson.com](http://nelsonjameson.com)