



## THE SLUDGE JUDGE® II — LARGE CAPACITY

- 1¼" (3.18 cm) outside diameter clear plastic butyrate tubing is very rigid when assembled
- Holds 6 oz. per foot (178 ml per .31 m)
- Float valve for easy sample collection and release
- Do not use in liquids over 165° F (74° C)

**B01355WA Sludge Judge® II Complete Unit.**

**B01358WA 5-ft. (1.53 m) Top Section with Rope.**

**B01357WA 5-ft. (1.53 m) Extension Section.**

**B01356WA 5-ft. (1.53 m) Bottom Section with Valve.**

## accessories



### A. CARRY BAG FOR SAMPLER

Holds four 5-ft. (1.52 m) sections of any Sludge Judge® product. Made of cotton canvas.

**C09249WA**

### B. CLEANING BRUSHES

The cleaning brush used with a mild detergent and warm water will keep the unit clear so accurate sludge readings can be taken. It is made of galvanized steel wire and polyester bristles. Disassemble the unit and clean each section separately.

**Cleaning Brush for Use for Sludge Judge® and Sludge Judge® Ultra.** 6 ft. (1.83 m) L. 1" (2.54 cm) dia. bristle.

**B01291WA**

**Cleaning Brush for The Sludge Judge® II.**

6 ft. (1.83 m) L. 1½" (3.81 cm) dia. bristle.

**B01361WA**