



Nitrile

## Offers tactility and comfortable protection across numerous applications

- Made of a soft nitrile formulation for comfortable fit and feel
- Lightweight construction for tactile sensitivity and fine motor control
- Designed for a broad range of applications across all industries
- Textured on the fingertips for secure handling of tools and materials



### Industries

- Healthcare
- Automotive
- Food Processing
- Janitorial / Sanitation
- Manufacturing
- Life Sciences
- Government

### Recommended For

- Standard patient examinations
- Picking parts and accessories
- Food processing and handling
- Catering/Meal preparation
- Disposal of waste (trash, biohazard and linens)
- Light assembly tasks
- Lab work, blending, compounding, filling, cleaning
- Preparing pharmaceutical products
- Laboratory analysis



## TECHNICAL DATA SHEET

### PRODUCT INFORMATION

|                                   | 92-134                                                                                                                                                                                                                                                                                                |
|-----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Material                          | Nitrile                                                                                                                                                                                                                                                                                               |
| Color                             | Blue                                                                                                                                                                                                                                                                                                  |
| Glove Design                      | Chlorinated, Powder-Free, Textured Fingers                                                                                                                                                                                                                                                            |
| Cuff                              | Beaded                                                                                                                                                                                                                                                                                                |
| Manufacturing/QMS Audit Standards | ISO 13485, ISO 9001                                                                                                                                                                                                                                                                                   |
| Regulatory                        | ASTM D6319, Category III, CE 0493, EN 16523-1, EN 455 1-4, EN ISO 21420:2020, EN ISO 374-1:2016, EN ISO 374-5:2016, FDA21 CFR 177-2600-US Food Contact Approved, Food Contact, IFU, ISO 13485, ISO 9001, Medical Device Regulation (EU) 2017/745 Class I, US QSR/FDA 510(k) Medical Examination Grade |
| Packaging                         | 100 gloves per dispenser, 10 dispensers per case, 1000 gloves per case   90 gloves per dispenser (Size XXL), 900 gloves per case (Size XXL)                                                                                                                                                           |
| Storage                           | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.                                                                                                                                                                                              |
| Country of Origin                 | China                                                                                                                                                                                                                                                                                                 |
| User Needs Segment                | Standard Thin                                                                                                                                                                                                                                                                                         |
| Available sizes                   | XS (5.5 - 6), S (6.5 - 7), M (7.5 - 8), L (8.5 - 9), XL (9.5 - 10)                                                                                                                                                                                                                                    |
| Anti-static                       | No                                                                                                                                                                                                                                                                                                    |

### PHYSICAL PROPERTIES

|                                         | Typical Values |             | Testing Method   |
|-----------------------------------------|----------------|-------------|------------------|
| Length (mm/inches)                      | 240 / 9.5      |             | ASTM D6319       |
| Freedom from Holes (Inspection level I) | 1.5 AQL        |             | ASTM D5151       |
| Palm Thickness (mm/mils)                | 0.07 / 2.8     |             | ASTM D6319       |
| Finger Thickness (mm/mils)              | 0.11 / 4.3     |             | ASTM D6319       |
|                                         | BEFORE AGING   | AFTER AGING |                  |
| Ultimate Tensile Strength (MPa)         | ≥ 14           | ≥ 14        | ASTM D412 & D573 |
| Elongation at Break (%)                 | ≥ 500          | ≥ 400       | ASTM D412 & D573 |
| Force at break (N)                      | ≥ 6            | ≥ 6         | EN 455-2         |

### ORDERING INFORMATION

| Size         | XS (5.5 - 6) | S (6.5 - 7) | M (7.5 - 8) | L (8.5 - 9) | XL (9.5 - 10) | XXL (10.5 - 11) |
|--------------|--------------|-------------|-------------|-------------|---------------|-----------------|
| Product Code | 92134060     | 92134070    | 92134080    | 92134090    | 92134100      | 92134110        |

### Performance Standards and Regulatory Compliance



Distributed by:

