

### SECTION 1: Identification

#### 1.1. Identification

|                |                        |
|----------------|------------------------|
| Product form   | : Substance            |
| Substance name | : Nitric Acid, 70% w/w |
| CAS-No.        | : 7697-37-2            |
| Product code   | : LC17700              |
| Formula        | : HNO <sub>3</sub>     |

#### 1.2. Recommended use and restrictions on use

|                              |   |
|------------------------------|---|
| Use of the substance/mixture | : Chemical raw material<br>Metal surface treatment<br>Printing industry: etch solution<br>Laboratory chemical |
| Recommended use              | : Laboratory chemicals  |
| Restrictions on use          | : Not for food, drug or household use   |

#### 1.3. Supplier

LabChem Inc  
Jackson's Pointe Commerce Park Building 1000, 1010 Jackson's Pointe Court  
Zelienople, PA 16063 - USA  
T 412-826-5230 - F 724-473-0647  
[info@labchem.com](mailto:info@labchem.com) - [www.labchem.com](http://www.labchem.com)

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 or 011-703-527-3887

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

|  |      |   |
|--|------|---|
| Oxidizing liquids Category 3                 | H272 | May intensify fire; oxidizer            |
| Corrosive to metals Category 1               | H290 | May be corrosive to metals              |
| Skin corrosion/irritation Category 1A        | H314 | Causes severe skin burns and eye damage |
| Serious eye damage/eye irritation Category 1 | H318 | Causes serious eye damage               |

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS03

GHS05

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H272 - May intensify fire; oxidizer  
H290 - May be corrosive to metals  
H314 - Causes severe skin burns and eye damage

Precautionary statements (GHS-US) :

P210 - Keep away from heat. - No smoking.  
P220 - Keep/Store away from clothing, combustible materials  
P221 - Take any precaution to avoid mixing with combustibles  
P234 - Keep only in original container.  
P260 - Do not breathe mist, spray, vapors.  
P264 - Wash exposed skin thoroughly after handling.  
P280 - Wear eye protection, face protection, protective clothing, protective gloves.  
P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated

# Nitric Acid, 70% w/w

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

clothing. Rinse skin with water/shower.  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P310 - Immediately call a poison center or doctor/physician.  
P363 - Wash contaminated clothing before reuse.  
P370+P378 - In case of fire: Use carbon dioxide (CO<sub>2</sub>), powder, alcohol-resistant foam to extinguish  
P390 - Absorb spillage to prevent material-damage.  
P405 - Store locked up.  
Dispose of contents/container in accordance with local, state and federal regulations.  
Store in corrosive resistant/... container with a resistant inner liner  
If inhaled: Remove person to fresh air and keep comfortable for breathing

### 2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification : None.

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Substance type : Multi-constituent

| Name                                       | Product identifier  | %   | GHS-US classification   |
|--|---------------------|-----|---|
| Nitric Acid, 70% w/w<br>(Main constituent) | (CAS-No.) 7697-37-2 | 100 | Ox. Liq. 3, H272<br>Met. Corr. 1, H290<br>Skin Corr. 1A, H314<br>Eye Dam. 1, H318 |

Full text of hazard classes and H-statements : see section 16

### 3.2. Mixtures

Not applicable

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general : Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with labored breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.

First-aid measures after inhalation : Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

First-aid measures after skin contact : Wash immediately with lots of water (15 minutes)/shower. Remove clothing while washing. Do not remove clothing if it sticks to the skin. Cover wounds with sterile bandage. Consult a doctor/medical service. If burned surface > 10%: take victim to hospital.

First-aid measures after eye contact : Rinse immediately with plenty of water for 15 minutes. Do not apply neutralizing agents. Cover eyes aseptically. Take victim to an ophthalmologist.

First-aid measures after ingestion : Rinse mouth with water. Immediately after ingestion: give lots of water to drink. Give milk to drink. Do not induce vomiting. Do not give activated charcoal. Do not give chemical antidote. Immediately consult a doctor/medical service. Call Poison Information Centre ([www.big.be/antigif.htm](http://www.big.be/antigif.htm)). Take the container/vomit to the doctor/hospital. Ingestion of large quantities: immediately to hospital.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : Irritation of the respiratory tract. Dry/sore throat. Corrosion of the upper respiratory tract. Coughing. FOLLOWING SYMPTOMS MAY APPEAR LATER: Respiratory difficulties. Possible inflammation of the respiratory tract. Risk of lung edema. Blue/grey discoloration of the skin.

Symptoms/effects after skin contact : Yellow skin. May stain the skin. Caustic burns/corrosion of the skin. Slow-healing wounds.

Symptoms/effects after eye contact : Corrosion of the eye tissue. Permanent eye damage.

Symptoms/effects after ingestion : Nausea. Vomiting. Abdominal pain. Burns to the gastric/intestinal mucosa. Possible esophageal perforation. Shock.

Chronic symptoms : ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Affection/dyscoloration of the teeth. Risk of pneumonia.

### 4.3. Immediate medical attention and special treatment, if necessary

Obtain medical assistance.

# Nitric Acid, 70% w/w

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Adapt extinguishing media to the environment.  
Unsuitable extinguishing media : No unsuitable extinguishing media known.

#### 5.2. Specific hazards arising from the chemical

- Fire hazard : DIRECT FIRE HAZARD. Non combustible. INDIRECT FIRE HAZARD. Promotes combustion. Reactions involving a fire hazard: see "Reactivity Hazard".  
Explosion hazard : INDIRECT EXPLOSION HAZARD. Reactions with explosion hazards: see "Reactivity Hazard".  
Reactivity : Concentrated solution reacts exothermically with water (moisture). Decomposes on exposure to temperature rise: release of toxic and corrosive gases/vapours (nitrous vapours). Violent to explosive reaction with many compounds e.g.: with (strong) reducers, with (some) bases, with organic material and with combustible materials with risk of spontaneous ignition. Reacts violently with (some) metals. Decomposes slowly on exposure to light: release of toxic and corrosive gases/vapours (nitrous vapours). Violent to explosive reaction with (some) metal powders: release of highly flammable gases/vapours (hydrogen).

#### 5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Cool tanks/drums with water spray/remove them into safety. Do not move the load if exposed to heat. Dilute toxic gases with water spray. Take account of toxic fire-fighting water. Use water moderately and if possible collect or contain it.  
Protection during firefighting : Use self-contained breathing apparatus and chemically protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Dike and contain spill. Absorb spillage to prevent material-damage.

##### 6.1.1. For non-emergency personnel

- Protective equipment : Gas-tight suit. Corrosion-proof suit. See "Material-Handling" to select protective clothing.  
Emergency procedures : Keep upwind. Mark the danger area. Consider evacuation. Seal off low-lying areas. Close doors and windows of adjacent premises. No naked flames. Corrosion-proof appliances. Keep containers closed. Wash contaminated clothes.

##### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection. Avoid breathing mist, spray.  
Emergency procedures : Stop leak if safe to do so. Ventilate area.

#### 6.2. Environmental precautions

- Prevent soil and water pollution. Prevent spreading in sewers.

#### 6.3. Methods and material for containment and cleaning up

- For containment : Contain released substance, pump into suitable containers. Consult "Material-handling" to select material of containers. Plug the leak, cut off the supply. Dam up the liquid spill. Try to reduce evaporation. Dilute toxic gases/vapours with water spray. Take account of toxic/corrosive precipitation water. Hazardous reaction: measure explosive gas-air mixture. Reaction: dilute combustible gas/vapour with water curtain.  
Methods for cleaning up : Take up liquid spill into inert absorbent material, e.g.: sand, earth, vermiculite or powdered limestone. Do not take up in combustible material such as: saw dust. Scoop absorbed substance into closing containers. See "Material-handling" for suitable container materials. Carefully collect the spill/leftovers. Spill must not return in its original container. Damaged/cooled tanks must be emptied. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

#### 6.4. Reference to other sections

- No additional information available

# Nitric Acid, 70% w/w

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Comply with the legal requirements. Remove contaminated clothing immediately. Clean contaminated clothing. Keep the substance free from contamination. Use corrosionproof equipment. Thoroughly clean/dry the installation before use. Do not discharge the waste into the drain. Never dilute by pouring water to the acid. Always add the acid to the water. Keep away from naked flames/heat. Observe very strict hygiene - avoid contact. Keep container tightly closed. Measure the concentration in the air regularly. Carry operations in the open/under local exhaust/ventilation or with respiratory protection.
- Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Incompatible products : combustible materials. metals. Strong bases. Strong reducing agents. wood.
- Incompatible materials : Combustible material. Direct sunlight. Metals.
- Heat-ignition : KEEP SUBSTANCE AWAY FROM: heat sources.
- Prohibitions on mixed storage : KEEP SUBSTANCE AWAY FROM: combustible materials. reducing agents. (strong) bases. cellulosic materials. organic materials. metal powders. water/moisture.
- Storage area : Store in a cool area. Keep out of direct sunlight. Store in a dry area. Store in a dark area. Ventilation at floor level. Fireproof storeroom. Keep locked up. Provide for a tub to collect spills. Aboveground. Keep only in the original container. Store only in a limited quantity. Meet the legal requirements.
- Special rules on packaging : SPECIAL REQUIREMENTS: hermetical. dry. clean. opaque. correctly labelled. meet the legal requirements. Secure fragile packagings in solid containers.
- Packaging materials : SUITABLE MATERIAL: stainless steel. aluminium. glass. MATERIAL TO AVOID: synthetic material.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

| Nitric Acid, 70% w/w (7697-37-2) |                                       |   |
|----------------------------------|---------------------------------------|---|
| ACGIH                            | ACGIH TWA (ppm)                       | 2 ppm (Nitric acid; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value) |
| ACGIH                            | ACGIH STEL (ppm)                      | 4 ppm (Nitric acid; USA; Short time value; TLV - Adopted Value)                         |
| OSHA                             | OSHA PEL (TWA) (mg/m <sup>3</sup> )   | 5 mg/m <sup>3</sup>   |
| OSHA                             | OSHA PEL (TWA) (ppm)                  | 2 ppm   |
| IDLH                             | US IDLH (ppm)                         | 25 ppm  |
| NIOSH                            | NIOSH REL (TWA) (mg/m <sup>3</sup> )  | 5 mg/m <sup>3</sup>   |
| NIOSH                            | NIOSH REL (TWA) (ppm)                 | 2 ppm   |
| NIOSH                            | NIOSH REL (STEL) (mg/m <sup>3</sup> ) | 10 mg/m <sup>3</sup>  |
| NIOSH                            | NIOSH REL (STEL) (ppm)                | 4 ppm   |

#### 8.2. Appropriate engineering controls

- Appropriate engineering controls : Emergency eye wash fountains should be available in the immediate vicinity of any potential exposure. Provide adequate general and local exhaust ventilation.

#### 8.3. Individual protection measures/Personal protective equipment

##### Personal protective equipment:

Protective goggles. Protective clothing. Face shield. Gloves. Combined gas/dust mask with filter type B/P2.



# Nitric Acid, 70% w/w

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Materials for protective clothing:

GIVE LESS RESISTANCE: polyethylene/ethylenevinylalcohol. GIVE POOR RESISTANCE: chloroprene rubber. nitrile rubber. polyethylene. PVA. natural fibres

### Hand protection:

Gloves

### Eye protection:

Safety glasses

### Skin and body protection:

Head/neck protection. Corrosion-proof clothing

### Respiratory protection:

Gas mask with filter type B. Gas mask with filter type E. Gas mask with filter type NO. High vapour/gas concentration: self-contained respirator

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|   |  |
|---|--|
| Physical state                                | : Liquid   |
| Appearance                                    | : Liquid.  |
| Color   | : Colourless-yellow On exposure to light: red-brown                            |
| Odor  | : Irritating/pungent odour Asphyxiating odour                                  |
| Odor threshold                                | : 0.29 - 0.98 ppm<br>0.75 - 2.5 mg/m <sup>3</sup>                              |
| pH  | : 1 (6 %)  |
| pH solution                                   | : 6 %  |
| Melting point                                 | : -42 - -38 °C   |
| Freezing point                                | : No data available  |
| Boiling point                                 | : 83 - 122 °C  |
| Flash point                                   | : Not applicable   |
| Relative evaporation rate (butyl acetate=1)   | : No data available  |
| Flammability (solid, gas)                     | : No data available  |
| Vapor pressure                                | : 7.3 - 58.5 hPa (20 °C)   |
| Relative vapor density at 20 °C               | : 2.2  |
| Relative density                              | : 1.4 - 1.5  |
| Relative density of saturated gas/air mixture | : 1.01   |
| Specific gravity / density                    | : 1413 - 1513 kg/m <sup>3</sup>  |
| Molecular mass                                | : 63.01 g/mol  |
| Solubility                                    | : Exothermically soluble in water. Soluble in ether.<br>Water: Complete        |
| Log Pow                                       | : -2.3 (OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method) |
| Auto-ignition temperature                     | : Not applicable   |
| Decomposition temperature                     | : No data available  |
| Viscosity, kinematic                          | : No data available  |
| Viscosity, dynamic                            | : 0.0009 - 0.002 Pa.s (20 °C)  |
| Explosion limits                              | : No data available  |
| Explosive properties                          | : No data available  |
| Oxidizing properties                          | : May intensify fire; oxidiser.  |

### 9.2. Other information

|                          |                       |
|--------------------------|-----------------------|
| Saturation concentration | : 10 g/m <sup>3</sup> |
| VOC content              | : 0 %                 |

# Nitric Acid, 70% w/w

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other properties : Gas/vapour heavier than air at 20°C. Hygroscopic. Producing fumes/mist. Physical properties depending on the concentration. Substance has acid reaction.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Concentrated solution reacts exothermically with water (moisture). Decomposes on exposure to temperature rise: release of toxic and corrosive gases/vapours (nitrous vapours). Violent to explosive reaction with many compounds e.g.: with (strong) reducers, with (some) bases, with organic material and with combustible materials with risk of spontaneous ignition. Reacts violently with (some) metals. Decomposes slowly on exposure to light: release of toxic and corrosive gases/vapours (nitrous vapours). Violent to explosive reaction with (some) metal powders: release of highly flammable gases/vapours (hydrogen).

#### 10.2. Chemical stability

Unstable on exposure to light. Hygroscopic.

#### 10.3. Possibility of hazardous reactions

May react violently with reducing agents.

#### 10.4. Conditions to avoid

Direct sunlight. Incompatible materials.

#### 10.5. Incompatible materials

Strong bases. Strong reducing agents. Organic compounds. cyanides. combustible materials. Aldehydes. Ammonia. metals. alcohols.

#### 10.6. Hazardous decomposition products

Nitrogen oxides. oxygen.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Likely routes of exposure : Inhalation; Skin and eye contact

Acute toxicity : Not classified

Skin corrosion/irritation : Causes severe skin burns and eye damage.  
pH: 1 (6 %)

Serious eye damage/irritation : Causes serious eye damage.  
pH: 1 (6 %)

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified  
(Based on available data, the classification criteria are not met)

Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : Not classified

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : Not classified

Symptoms/effects after inhalation : Irritation of the respiratory tract. Dry/sore throat. Corrosion of the upper respiratory tract. Coughing. FOLLOWING SYMPTOMS MAY APPEAR LATER: Respiratory difficulties. Possible inflammation of the respiratory tract. Risk of lung edema. Blue/grey discolouration of the skin.

Symptoms/effects after skin contact : Yellow skin. May stain the skin. Caustic burns/corrosion of the skin. Slow-healing wounds.

Symptoms/effects after eye contact : Corrosion of the eye tissue. Permanent eye damage.

Symptoms/effects after ingestion : Nausea. Vomiting. Abdominal pain. Burns to the gastric/intestinal mucosa. Possible esophageal perforation. Shock.

Chronic symptoms : ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Affection/discolouration of the teeth. Risk of pneumonia.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : Classification concerning the environment: not applicable.

Ecology - air : Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009).

# Nitric Acid, 70% w/w

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ecology - water : Maximum concentration in drinking water: 50 mg/l (nitrate) (Directive 98/83/EC). Harmful to fishes. Slightly harmful to invertebrates (Daphnia). May cause eutrophication. pH shift.

| Nitric Acid, 70% w/w (7697-37-2) |                       |
|----------------------------------|-----------------------|
| EC50 Daphnia 1                   | 180 mg/l (EC50; 48 h) |
| LC50 fish 2                      | 72 ppm (LC50; 96 h)   |
| Threshold limit algae 1          | > 19 mg/l (EC0)       |

### 12.2. Persistence and degradability

| Nitric Acid, 70% w/w (7697-37-2) |   |
|----------------------------------|---|
| Persistence and degradability    | Biodegradability: not applicable. No test data on mobility of the components available. |
| Biochemical oxygen demand (BOD)  | Not applicable  |
| Chemical oxygen demand (COD)     | Not applicable  |
| ThOD                             | Not applicable  |

### 12.3. Bioaccumulative potential

| Nitric Acid, 70% w/w (7697-37-2) |  |
|----------------------------------|--|
| BCF fish 1                       | <= 1 (BCF)   |
| Log Pow                          | -2.3 (OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method) |
| Bioaccumulative potential        | Bioaccumulation: not applicable.   |

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste disposal recommendations : Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Recycle/reuse. Remove for physico-chemical/biological treatment. Remove to an authorized dump (Class I). Treat using the best available techniques before discharge into drains or the aquatic environment.

Additional information : LWCA (the Netherlands): KGA category 01. Hazardous waste according to Directive 2008/98/EC.

## SECTION 14: Transport information

### Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN2031 Nitric acid (other than red fuming, with at least 65 percent, but not more than 70 percent nitric acid), 8, II

UN-No.(DOT) : UN2031

Proper Shipping Name (DOT) : Nitric acid  
other than red fuming, with at least 65 percent, but not more than 70 percent nitric acid

Transport hazard class(es) (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Packing group (DOT) : II - Medium Danger

Hazard labels (DOT) : 8 - Corrosive  
5.1 - Oxidizer



DOT Packaging Non Bulk (49 CFR 173.xxx) : 158

# Nitric Acid, 70% w/w

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|  |  |
|--|--|
| DOT Packaging Bulk (49 CFR 173.xxx)                              | : 242  |
| DOT Special Provisions (49 CFR 172.102)                          | : A6 - For combination packaging, if plastic inner packaging are used, they must be packed in tightly closed metal receptacles before packing in outer packaging.<br>B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized.<br>B47 - Each tank may have a reclosing pressure relief device having a start-to-discharge pressure setting of 310 kPa (45 psig).<br>IP15 - For UN2031 with more than 55% nitric acid, rigid plastic IBCs and composite IBCs with a rigid plastic inner receptacle are authorized for two years from the date of IBC manufacture.<br>T8 - 4 178.274(d)(2) Normal..... Prohibited<br>TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively. |
| DOT Packaging Exceptions (49 CFR 173.xxx)                        | : None   |
| DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) | : Forbidden  |
| DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)     | : 30 L   |
| DOT Vessel Stowage Location                                      | : D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.  |
| DOT Vessel Stowage Other   | : 66 - Stow "separated from" flammable solids,74 - Stow "separated from" oxidizers,89 - Segregation same as for oxidizers,90 - Stow "separated from" radioactive materials   |
| Other information  | : No supplementary information available.  |

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

| Nitric Acid, 70% w/w (7697-37-2)   |  |
|--|--|
| Listed on the United States TSCA (Toxic Substances Control Act) inventory<br>Subject to reporting requirements of United States SARA Section 313 |  |
| RQ (Reportable quantity, section 304 of EPA's List of Lists)   | 1000 lb  |
| SARA Section 302 Threshold Planning Quantity (TPQ)   | 1000 lb  |
| SARA Section 311/312 Hazard Classes  | Physical hazard - Oxidizer (liquid, solid or gas)<br>Physical hazard - Corrosive to metals<br>Health hazard - Skin corrosion or Irritation<br>Health hazard - Serious eye damage or eye irritation |

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

|                      |                   |      |
|----------------------|-------------------|------|
| Nitric Acid, 70% w/w | CAS-No. 7697-37-2 | 100% |
|----------------------|-------------------|------|

#### 15.2. International regulations

##### CANADA

No additional information available

##### EU-Regulations

No additional information available

##### National regulations

No additional information available

#### 15.3. US State regulations

# Nitric Acid, 70% w/w

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations


California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

### SECTION 16: Other information

Revision date : 01/10/2018

Full text of H-phrases: see section 16:

|      |   |
|------|---|
| H272 | May intensify fire; oxidizer            |
| H290 | May be corrosive to metals              |
| H314 | Causes severe skin burns and eye damage |
| H318 | Causes serious eye damage               |

|                      |   |   |
|----------------------|---|---|
| NFPA health hazard   | : 4 - Materials that, under emergency conditions, can be lethal.  |  |
| NFPA fire hazard     | : 0 - Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand.                               |   |
| NFPA reactivity      | : 0 - Material that in themselves are normally stable, even under fire conditions.  |   |
| NFPA specific hazard | : OX - Materials that possess oxidizing properties.   |   |
| Hazard Rating        |   |   |
| Health               | : 4 Severe Hazard - Life-threatening, major or permanent damage may result from single or repeated overexposures  |   |
| Flammability         | : 0 Minimal Hazard - Materials that will not burn   |   |
| Physical             | : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives. |   |
| Personal protection  | : H<br>H - Splash goggles, Gloves, Synthetic apron, Vapor respirator  |   |

SDS US LabChem

*Information in this SDS is from available published sources and is believed to be accurate. No warranty, express or implied, is made and LabChem Inc assumes no liability resulting from the use of this SDS. The user must determine suitability of this information for his application.*