

# Universal Centrifuge

| Z307



**HERMLE**  
**Benchmark** 

4 x 200 ml

# Z307



The Z307 compact universal laboratory centrifuge offers a wide range of applications covering clinical, research, and industrial laboratory use. The Z307 offers many accessories, including rotors for microplates and high speed fixed angle rotors for microtubes and centrifuge tubes up to 50 ml. The swing out rotors can load all common tubes such as blood collection tubes, 15/50 ml tubes and even 200 ml tubes. This wide range of accessories makes the Z307 laboratory centrifuge indispensable in research laboratories and clinical hospital laboratories.

## Technical Data

max. Speed:	14,000 rpm
max. RCF:	18,624 xg
max. Volume:	4 x 200 ml
Speed range:	200 – 14,000 rpm
Running time:	59 min 50 s / 10 s increments 99 h 59 min / 1 min increments
Dimensions:	14 in x 13 in x 18.6 in 35.5 cm x 33 cm x 47.4 cm (W x H x D)
Weight:	66 lbs / 30 kg
Order No:	Z307, 120 V 50 - 60 Hz / 240 W Z307-E, 230 V 50 - 60 Hz / 300 W



## Specifications

- Maintenance-free induction drive
- Microprocessor with large LCD display
- Lid lock
- Automatic radio-frequency rotor identification system (RFID) with over speed protection, immediately upon rotor insertion
- Active imbalance identification and cut-off (rotor-specific)
- Imbalance tolerant drive
- A large variety of rotors and accessories
- Manufactured according to international safety regulations, i.e. IEC 61010
- Audible signal at the end of each run with several melody options
- Rotor exchange is easy to handle
- Noise level under 63 dBA at max. speed
- Improved ventilation system keeps samples cool
- Stainless steel chamber

## Distinct Control Panel

- Simple one handed Touch-Operation
- Easy to program with gloves on
- Splash proof digital display
- Permanent indication of Preset and Actual Values
- Selection of speed in both rpm and g-force, with increments of 10
- 10 acceleration and 10 deceleration rates, Possibility of brakeless deceleration
- Pre-selection of running time from 10 s to 99 h 59 min or continuous
- Storage of up to 99 runs incl. rotor type
- Quick-key for short runs
- Diagnostic program
- Color visual representation of the operating state such as run completed, standby or centrifugation

# Accessories Z307

## Rotor/Bucket

Order No.:  
**Z327-200**

Swing out rotor 4 Place w/ buckets  
Angle: 0-90°  
(w/o buckets: Z327-200-AC)

Z327-200-BUK  
Bucket for Adapter

Z327-200-LID  
Lid for Bucket | hermetically sealed



## Adapter

Acceleration in s: 17/97  
Deceleration in s: 14/256  
max. Speed: 4,500 rpm  
RCF-value: 3,350 xg  
max. Radius: 14.8 cm

Volume  
Tubes Ø in mm

200 ml  
Bottle  
56



112  
4  
0.0  
without Adapter

200 ml  
conical  
56



120  
4  
0.0  
A200

100 ml  
RB Glass  
40



95/115  
4  
0.2  
A100

85 ml  
RB/OR  
38



95/108  
4  
0.2  
A85

Length min./max. (mm)  
Tubes per rotor  
Radius correction (cm)  
Order No. Adapter: Z327-200-\_\_\_\_

Volume  
Tubes Ø in mm

50 ml  
RB/OR  
29



95/103  
4  
0.2  
A50R

50 ml  
conical  
29



116  
4  
0.1  
A50

50 ml  
skirted  
29



116  
4  
0.2  
A50SS

25/30 ml  
Universal  
25



95/105  
4  
0.2  
A25

25/30 ml  
RB/OR  
25



90/110  
4  
0.2  
A30

15 ml  
conical  
17



120  
16  
0.1  
A15B\*

15 ml  
conical  
17



120  
12  
0.0  
A15

15 ml  
RB  
17



60/107  
28  
0.2  
A15R

5/7 ml  
RB  
13



65/100  
32  
0.2  
A57

5 ml  
conical  
17



60/70  
20  
0.1  
A5F

1.5/2.0 ml  
micro  
11



40  
32  
0.1  
A20

6-10 ml  
Vakut.®  
16



130  
4  
0.2  
A15L

6-10 ml  
Vakut.®  
16



100  
28  
0.2  
A10

1.8-7 ml  
Vakut.®  
13



75/100  
32  
0.2  
A57

50 ml  
conical  
29



116  
8  
0.0  
B50

Length min./max. (mm)  
Tubes per Rotor  
Radius correction (cm)  
Order No. Adapter: Z327-200-\_\_\_\_

\*only without Bucket Lid

Order No.:  
**Z326-100H**

Swing out rotor 4 Places  
w/ sealed buckets  
Angle: 0-90°

Z326-100H-BUK  
Bucket for Tube Rack w/ lid

Z326-100H-LID  
Lid for bucket



Acceleration in s: 15/100  
Deceleration in s: 15/150  
max. Speed: 4000 rpm  
RCF-value: 2611 xg  
max. Radius: 14.6 cm

Volume  
Tubes ø in mm

100 ml  
RB Glass  
40



90/108  
4  
0.9  
A100

85 ml  
RB/OR  
38



90/108  
4  
0.6  
A85

50 ml  
RB/OR  
29



90/133  
4  
0.6  
A50R

50 ml  
Falcon®  
29



116  
4  
0.4  
A50

Length min./max. in mm  
Tubes per rotor  
Radius correction (cm)  
Order-No.: Z326-100H-\_\_\_\_

Volume

Tubes Ø in mm

50 ml  
skirted  
29



116  
4  
0.7  
A50SS

30 ml  
Universal  
25



95/105  
4  
1.5  
A30

15 ml  
Falcon®  
17



120  
4  
0.5  
A15S

15 ml  
Falcon®  
17



120  
8  
0.5  
A15\*

15 ml  
RB Glass  
17



90/108  
16  
0.6  
A15R

6-10 ml  
Vakut.®  
16



75/100  
16  
0.6  
A10

10-15 ml  
Vakut.®  
16



75/125  
4  
0.6  
A15L\*

1.8-7 ml  
Vakut.®  
13



75/100  
16  
0.6  
A57

1.5 ml  
Reakt.  
11



42  
20  
0.6  
A20

50 ml  
Falcon®  
29



116  
8  
0.0  
B50

15 ml  
Falcon®  
17



120  
12  
0.0  
B15

Length min./max. (mm)  
Tubes per rotor  
Radius Correction (cm)  
Order No. Tube rack

\* only without bucket lid

Order No.:  
**Z306-100**



Swing out rotor 4 Places  
Angle: 0-90°

Acceleration in s: 13/110  
Deceleration in s: 18/158  
max. Speed: 4,500 rpm  
RCF-value: 3,350 xg  
max. Radius: 14.8 cm

Volume  
Tubes Ø in mm

145 ml  
Nalgene®  
50



100  
4  
1.0  
A145

100 ml  
RB Glass  
44



90/108  
4  
1.0  
A100

85 ml  
RB/OR  
38



90/108  
4  
0.8  
A85

50 ml  
RB Glass  
29



90/118  
4  
0.7  
A50R

50 ml  
conical  
29



116  
4  
0.3  
A50

Length min./max. (mm)  
Tubes per Rotor  
Radius correction (cm)  
Order No. Adapter: Z306-100-\_\_\_\_

Volume

Tubes Ø in mm

50 ml  
skirted  
29



116  
4  
0.6  
A50SS

30 ml  
Universal  
25



95/105  
4  
1.1  
A30

15 ml  
conical  
17



120  
8  
0.0  
A15

15 ml  
RB  
17



90/108  
28  
0.4  
A57

6-10 ml  
Vakut.®  
16



90/108  
28  
0.4  
A10

1.8-7 ml  
Vakut.®  
13



75/100  
28  
0.7  
A57

5/7 ml  
RB Glass  
13



75/100  
36  
1.3  
A57B

1.5/2.0 ml  
micro  
11



40  
40  
5.5  
A20

Length min./max. (mm)  
Tubes per Rotor  
Radius correction (cm)  
Order No. Adapter: Z306-100-\_\_\_\_

Order No.:  
**Z326-02MP**












Swing out rotor 2x3 Microplates  
Angle: 0-90°

Acceleration in s: 24/220  
Deceleration in s: 24/339  
max. Speed: 4,500 rpm  
RCF-value: 2,716 xg  
max. Radius: 12.0 cm  
max. Loading height: 63 mm  
max. Loading weight: 310 g


Order No.:  
BT1500-A1520  
BT1500-A05  
Z326-MPCA

Tube rack  
20 x 1.5 ml (2.0ml) Tubes  
20 x 0.5 ml  
3 x Chamber Slide or 30/60 mm petri dish

# Accessoires Z307

Rotor/Bucket		Adapter				
<div>Order No.: Z326-3015</div> <div></div> <div>Angle rotor 30 x 15 ml Glass or 20 x 15 ml conical Angle: 35°</div>	<div>Acceleration in s: 18/155 Deceleration in s: 18/369 max. Speed: 4,500 rpm RCF-value: 2,830 xg max. Radius: 12.5/10.9 cm max. Ø: 17 mm</div>	<div>Order No.: without without C3100-ADP</div>	<div>Adapter 1 x 15ml Glass 1 x 15ml conical 1 x 5/7ml</div>	<div>Ø [mm] 17.0 17.0 13</div>	<div>Length [min./max.]: 95/115 120 75/100</div>	
<div>Order No.: Z326-1215</div> <div></div> <div>Angle rotor 12 x 15 ml Angle: 32°</div>	<div>Acceleration in s: 13/101 Deceleration in s: 11/285 max. Speed: 6,000 rpm RCF-value: 4,427 xg max. Radius: 11.0 cm max. Ø: 17 mm</div>	<div>Volume</div> <div></div> <div>Tubes Ø in mm Length min./max. in mm Order No. Adapter</div>	<div>15 ml conical 15 ml 4-7ml Vakut.® 1.8-5 ml Vakut.®</div> <div>17 120 without 17 105/120 without 13 100 C3100-ADP 13 75 C3100-ADP</div>			
<div>Order No.: Z326-0650-LS</div> <div></div> <div>Angle rotor 6 x 50 ml Angle: 40°</div>	<div>Acceleration in s: 14/102 Deceleration in s: 11/304 max. Speed: 6,000 rpm RCF-value: 4,424 xg max. Radius: 11.0 cm max. Ø: 29 mm</div>	<div>Volume</div> <div></div> <div>Tubes Ø in mm Length min./max. in mm Order No. Adapter</div>	<div>50 ml conical 50 ml RB/OR 15 ml conical 7 ml 5 ml</div> <div>29 116 without 29 100/120 without 17 120 Z206-50-A15 17 97/120 Z206-50-A57 18 100/105 Z206-50-A57C* *with Z206-50-A57</div>			
<div>Order No.: Z326-1205</div> <div></div> <div>Angle rotor 12 x 5 ml Tubes Angle: 45°</div>	<div>Acceleration in s: 27/238 Deceleration in s: 22/206 max. Speed: 14,000 rpm RCF-value: 18,624 xg max. Radius: 8.5 cm max. Ø: 11 mm</div>	<div>Order No.: without Z216-05-C10 Z216-05-C18</div>	<div>Adapter 1 x 5.0ml conical 1 x 1.0ml Cryo, flat 1 x 1.8ml Cryo, round</div>	<div>Ø [mm] 17 12.6 12.6</div>	<div>Length [min./max.]: 60 41 48</div>	
<div>Order No.: Z326-2420</div> <div></div> <div>Plastic-Lid Angle rotor 24 x 1.5/2.0 ml Angle: 45°   hermetically sealed</div>	<div>Acceleration in s: 23/207 Deceleration in s: 34/215 max. Speed: 14,000 rpm RCF-value: 18,624 xg max. Radius: 8.5 cm max. Ø: 11 mm</div>	<div>Order No.: without without C1008-A5-6 C1008-A2-6</div>	<div>Adapter 1 x 2.0 ml 1 x 1.5 ml 1 x 0.5 ml 1 x 0.4/0.2 ml PCR</div>	<div>Ø [mm] 11 11 8 6</div>	<div>Length [min./max.]: 40 40 45 45</div>	
<div>Order No.: Z326-2420H</div> <div></div> <div>Aluminum-Lid Angle rotor 24 x 1.5/2.0 ml Angle: 45°   hermetically sealed</div>	<div>Acceleration in s: 23/206 Deceleration in s: 33/196 max. Speed: 14,000 rpm RCF-value: 18,624 xg max. Radius: 8.5 cm max. Ø: 11 mm</div>	<div>Order No.: without without C1008-A5-6 C1008-A2-6</div>	<div>Adapter 1 x 2.0 ml 1 x 1.5 ml 1 x 0.5 ml 1 x 0.4/0.2 ml PCR</div>	<div>Ø [mm] 11 11 8 6</div>	<div>Length [min./max.]: 40 40 45 45</div>	
<div>Order No.: Z326-3020H</div> <div></div> <div>Angle rotor 30 x 1.5/2.0 ml Angle: 45°</div>	<div>Acceleration in s: 26/244 Deceleration in s: 33/349 max. Speed: 12,000 rpm RCF-value: 15,131 xg max. Radius: 9.4 cm max. Ø: 11 mm</div>	<div>Order No.: without without C1008-A5-6 C1008-A2-6</div>	<div>Adapter 1 x 2.0 ml 1 x 1.5 ml 1 x 0.5 ml 1 x 0.4/0.2 ml PCR</div>	<div>Ø [mm] 11 11 8 6</div>	<div>Length [min./max.]: 40 40 45 45</div>	

Distributed by:



Distributed by:

**NELSON JAMESON**  
INC.

800-826-8302 nelsonjameson.com

www.HermleUSA.com  
PH: 908-769-5555  
EM: info@benchmarkscientific.com

Technical modification rights reserved. V 10/21