



Nitrile

Nitrile exam gloves with excellent dexterity along with enhanced comfort, fit and feel

- **Thin durable design:** Offers strength, dexterity and tactility
- **Black nitrile:** Hides oils, bodily fluids and other stains
- **ERGOFORM™ Technology:** Ergonomic design supports musculoskeletal health



Industries

- Food Service
- Cosmetics
- Tattoo
- Automotive Aftermarket
- Chemical
- Emergency Medical Services
- Healthcare
- Law Enforcement
- Life Sciences
- Dental
- Machinery and Equipment
- Metal fabrication

Recommended For

- General dentistry
- Standard patient examinations
- Emergency services
- Catering/Meal preparation
- General Purpose Auto Aftermarket
- Equipment repair and maintenance
- Laboratory analysis
- Cosmetic Procedures
- Tattoo



TECHNICAL DATA SHEET

| | Product Information |
|------------------------|--|
| External Glove Surface | Textured Fingers |
| Audit Standards | 21 CFR 820, ISO 13485, ISO 9001 |
| Product Certification | Medical Device Regulation (EU) 2017/745 Class I, Personal Protective Equipment Regulation (EU) 2016/425 Category III risks |
| Packaging Overview | Case=1000 gloves/10 dispensers; Dispenser=100 gloves 2XL: Case=900 gloves/10 dispensers; Dispenser=90 gloves |
| Storage Instructions | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition. |
| Country Of Origin | China |
| Product Segmentation | High Touch |
| Antistatic | No |


PHYSICAL PROPERTIES

| | Typical Values | | Testing Method |
|---|----------------|-------------|----------------------|
| Length (mm/inches) | 245 / 9.6 | | ASTM D6319, EN 455-2 |
| Freedom from Holes (Inspection level I) | 1.5 AQL | | ASTM D5151, EN 455-1 |
| Palm Thickness (mm/mils) | 0.07 / 2.8 | | ASTM D6319, EN 455-2 |
| Finger Thickness (mm/mils) | 0.11 / 4.3 | | ASTM D6319, EN 455-2 |
| | BEFORE AGING | AFTER AGING | |
| Ultimate Tensile Strength (MPa) | ≥ 18 | ≥ 16 | ASTM D412 & D573 |
| Elongation at Break (%) | ≥ 500 | ≥ 400 | ASTM D412 & D573 |
| Force at break (N) | ≥ 6 | ≥ 6 | EN 455 |

ORDERING INFORMATION

| Size | XS (5.5 - 6) | S (6.5 - 7) | M (7.5 - 8) | L (8.5 - 9) | XL (9.5 - 10) | XXL (10.5 - 11) |
|--------------|--------------|-------------|-------------|-------------|---------------|-----------------|
| Product Code | 93732060 | 93732070 | 93732080 | 93732090 | 93732100 | 93732110 |

Performance Standards and Regulatory Compliance



Distributed by:



Technology



Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending; www.ansell.com/patentmarking © 2022 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

