



AUTOMATIC SCRUBBERS - WALK BEHIND

CT105

The CT105 is recommended for medium sized spaces and has been designed to be very easy to use, while keeping electronics to a minimum. Featuring constant flow technology, for full control of water flow, a large brush head and an "oversized" output of the dirt water tank, the CT105 is the most reliable, productive and simple machine in its category.

MAX PRODUCTIVITY

27,000-
31,000 ft²/h

BATTERIES
RUNNING TIME

2.5-6.0 h

KEY SPECS

26/27 gal
28", 32"
traction drive

MOST FREQUENT USE

RETAIL



HOSPITALITY



CLEANING CONTRACTORS



EDUCATION



NEW LARGE COVER



NEW ERGONOMIC HANDLE



HIGH QUALITY MOTOR GEAR BOX



INNOVATIONS




SLS™
SELF
LEVELING
SYSTEM

CONSTANT CLEANING PERFORMANCE

ELECTRONIC SYSTEM



INNOVATION



SELF- LEVELLING SYSTEM

DETAILS

- The brush pressure with self-leveling and self-adjusting head, allows a perfect fit between the brush and floor
- System available as mechanical, electro mechanical or electronic according to machine models

MACHINES

- Available on all machines models

CT105



Other Features

- (CFS) Central Flow System solution distribution from brush center
- CWS (Constant Weight System) ensures maximum scrubbing results
- Exclusive squeegee system assures high performance at low cost
- High quality/ high performance vacuum motor
- Great maneuverability due to optimum weight distribution
- Squeegee blade can be used on 4 sides before replacement
- Easy access to internal components
- Designed to assure minimum noise levels
- Battery level indicator
- On board charger and external battery charger plug
- Inlet and outlet filters for maximum tank protection
- (AFS) Anti Foam System and shut off sensor protect vacuum
- Squeegee assembly and blade replacement without tools

CT105 TECHNICAL SPECIFICATIONS

		CT105 TRACTION	CT105 TRACTION
Code		CT105 BT70	CT105 BT85
PRODUCTIVITY			
Max theoretical productivity	ft ² /h - m ²	27,000 ft ² /3,150 m ²	31,000 ft ² /3,825 m ²
Cleaning path	in/mm	28 in/ 700 mm	32 in/ 850 mm
Cleaning path	in/mm	37 in/ 950 mm	37 in/ 950 mm
Water tank capacity	Gal/ l	26/27 gal/ 100/110 l	26/27 gal/ 100/110 l
Max running time	min	360	360
Voltage	V-Ah	24V (4x6)	24V (4x6)
Installed power	W	650	650
Max Speed		2.8 mph/ 4.5 kmh	2.8 mph/ 4.5 kmh
Brush pressure	lbs/ kg	148 lbs/ 67 kg	152 lbs/ 63 kg
Weight	lbs/ kg	756 lbs/ 343 kg	820 lbs/ 372 kg
Dimensions	in	63 x 29 x 42 in	64 x 35 x 42 in

AVAILABLE ACCESSORIES

PAD DRIVER
SPPV01228 (14"),
SPPV01234 (16")



NYLON BRUSH
SPPV01472 (14"),
SPPV01516 (16")



TYNEX BRUSH
SPPV01475 (14"),
SPPV01517 (16")



NATURAL BRISTLE BRUSH
SPPV01478 (14"),
SPPV01385 (16")



ON-BOARD CHARGER
KTRI01915



6225V AGM
6V225-AGM



6V240AH
6V240



6V325AH
6V325



6V330 AGM
6V330-AGM



BATTERY WATERING SYSTEM
CR-BWS-L-4



CHARGER WET/ GEL
BACA00136



SQUEEGEES
PMVR02239 (COMPLETE)
MPVR08040 (FRONT)
MPVR08036 (REAR)



GET RIGHT SIZED

	Description	Continuous run-time	Theoretical ft ² / h	Maximum Theoretical ft ² /charge	Ft ² charge efficiency (70%)
CT105BT70	Traction Drive, 240ah Battery	3.7 h	26,988	99,857	69,900
CT105BT70	Traction Drive 325ah Battery	5.0 h	26,988	134,942	94,459
CT105BT70	Traction Drive, 225 AGM Battery	3.7 h	26,988	99,857	69,900
CT105BT70	Traction Drive 330ah Battery	5.0 h	26,988	134,942	94,459
CT105BT85	Traction Drive, 240ah Battey	3.7 h	30,844	114,122	79,885
CT105BT85	Traction Drive, 325ah Battery	5.0 h	30,844	154,219	107,953
CT105BT85	Traction Drive 225 AGM Battery	3.7 h	30,844	114,122	79,885
CT105BT85	Traction Drive 330ah Battery	5.0 h	30,844	154,219	107,953



Distributed by:

NELSON JAMESON
INC.
800-826-8302 nelsonjameson.com