PRODUCT INFORMATION

ULTRA 1000 (#1225)

PRODUCT DESCRIPTION

ULTRA 1000 is a premium, heavy duty, liquid alkaline detergent formulated expressly for use in cleaning heavily soiled equipment and pipelines and food-borne soils typically found in food processing plants. Formulated for use in pipelines, boil out, spray, soak and CIP operations where carbon, heavy burn-on, grease, oil, blood and fat must be removed.

ULTRA 1000 contains a blend of sodium hydroxide, hard water mineral sequestrants, wetting agents, rinse agents, alkaline builders and alkaline salts.

FEATURES AND BENEFITS

- Concentrated
- Chelated
- Highly Alkaline
- Contains Water Conditioners
- Economical to Use
- Minimizes Scale Formation
- Removes Carbonized and Organic Soils
- Rinses Freely
- Suitable for Circulation Cleaning

USES AND APPLICATIONS

ULTRA 1000 can be used in red meat and pork packing plants, poultry slaughter and further processing plants, dairies, cheese plants canning plants, and other food processing plants. Especially effective re-circulation in high temperature process units, boil out vats, cookers, kettles, parts washers, CIP line re-circulation and smokehouses.

ULTRA 1000 is safe for use on most plastics, teflon, HDPE, stainless steel, plain steel, fiber wall panels and ceramic tile. Not recommended for use on, aluminum, galvanized (zinc coated), tin, copper, bronze or other soft metals.

Distributed by:
NELSON JAMESON INC.
800-826-8302 nelsonjameson.com

It is acknowledged that the application of the inf he information obsolete or inaccurate. Although we believe the information shown is accurate, Hydrite shall not be liable with respect to the application or use of any of the information. HYDRITE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MARKETABILITY OR FITNESS FOR A PARTICULAR

PRODUCT INFORMATION

- CIP CIRCULATION: Circulate a solution of 0.30-1.50 oz/gal at 140-180°F for 30 minutes.
- BOIL-OUT: Generally 2.0-4.0 oz/gallon
- This product can be used at higher usage levels than listed for heavy soil loads, burnt on soils, or other conditions where more chemical is required to remove the soil

Consult your Hydrite representative for specific recommendations

TYPICAL VALUES

Appearance:	Clear, brown liquid
pH, as is:	>13
Specific gravity @ 25°C:	1.494
Foam:	Low

PRECAUTIONS

Product safety information and handling precautions are contained on the product label and Material Safety Data Sheet (MSDS).

READ AND UNDERSTAND LABEL AND MATERIAL SAFETY DATA SHEET BEFORE PRODUCT USE.

FP3262
3/1/4
REV. 3

Distributed by:
NELSON JAMESON INC.
800-826-8302 nelsonjameson.com

It is acknowledged that the application of the inf he information obsolete or inaccurate. Although we believe the information shown is accurate, Hydrite shall not be liable with respect to the application or use of any of the information. HYDRITE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MARKETABILITY OR FITNESS FOR A PARTICULAR