

KLEENGUARD™ A40 Shoe and Boot Covers

Product Information

Boot cover	Code	Size	Qty
	44491	Universal	400 ea



- Serged seams
- Elastic opening
- 17" height
- Seamless sole
- White
- One size fits all

Boot Cover	Code	Size	Qty
	36779	M/L	400 ea
	44495	XL/2XL	400 ea



- Serged seams
- Elastic top
- Elastic at ankle
- Highly durable sole
- 18" height
- White

Shoe Cover	Code	Size	Qty
	27000	Universal	300 ea



- Serged seams
- Elastic opening
- 7" height
- Seamless sole
- White
- One size fits all

Shoe Cover	Code	Size	Qty
	44490	Universal	400 ea



- Serged seams
- Fully elasticized for formed fit
- 7" height
- White
- One size fits all

Shoe Cover	Code	Size	Qty
	44492	M/L	400 ea
	44494	XL/2XL	400 ea



- Serged seams
- Elastic Top
- Highly durable sole
- 5.25" height
- White

A40 Fabric Properties

Physical Properties	Test Methods	Target
Tensile Strength (MD)	ASTM D5034	39 lb-f
Tensile Strength (CD)	ASTM D5034	22 lb-f
Trapezoidal Tear (MD)	INDA IST 100.2	14 lb-f.
Trapezoidal Tear (CD)	INDA IST 100.2	7 lb-f.
Elongation (MD)	ASTM D5034	70%
Elongation (CD)	ASTM D5034	80%
Lint -# of particles [†]	IEST-RP-003.4 Helmke Drum	>0.3µm - 3593 >0.5µm - 3109
Flammability	CPSC 1610	Class 1
Static Decay (<0.5 sec)	NFPA 99	Pass

[†]Benchmark testing, sample = 1

Barrier Properties	Test Methods	Target
Hydrohead	AATCC 127-1998	187 cm
Particle Holdout (0.3-0.5 µm)	Independent Lab.	99.9%

Additional Attributes

- Microporous film laminate provides particle and liquid barrier
- Product not made with silicone
- Made with non-latex elastic
- Serged seams

High Traction Sole Properties (36779, 44495, 44492, 44494)

Physical Properties	Test Methods	Target
Tensile Strength (MD)	ASTM D5034	72.4 lb-f
Tensile Strength (CD)	ASTM D5034	69.6 lb-f
Trapezoidal Tear (MD)	INDA IST 100.2	23.4 lb-f
Trapezoidal Tear (CD)	INDA IST 100.2	22.5 lb-f
Elongation (MD)	ASTM D5034	60.7%
Elongation (CD)	ASTM D5034	68.8%
Lint - # of particles (>0.5 µm)	IEST-RP-CC003.4 Helmke Drum	Category 2
Flammability	CPSC 1610	Class 1
Static COF (Dry Stainless Steel)	ASTM D1894-78	14.5
Dynamic COF (Dry, Stainless Steel)	ASTM D1894-78	4.5

Workmanship Requirements: Apparel shall be made in accordance with reasonable industry practice with respect to holes, tears, wrinkles, cleanliness, and foreign materials or dirt.

It is the responsibility of the user to assess the type of hazard and the risk associated with exposure and then decide in the appropriate personal protective equipment needed for each circumstance. Failure to use only KLEENGUARD™ designed produced and tested components, attachments and replacement parts can adversely affect product performance resulting to serious injury.

For additional information visit us at www.KCProfessional.com or contact us at 888-346-GOKC (4652)

Storage	Store in a cool, dry place.
Country of Origin	Mexico
Disposal	Dispose of in accordance with local authority regulations.

Distributed by:

NELSON JAMESON INC.
800-826-8302 nelsonjameson.com

Rev. 4/2019

Kimberly-Clark warrants that its products (1) comply with K-C's standard specifications as of the delivery date to K-C's authorized distributors/direct purchasers (2) comply with all K-C labeling representations; and (3) are manufactured in compliance with all applicable federal, state, and local laws in effect at the time and place of manufacture of the products. **THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** K-C is not liable for any kind of special, incidental, or consequential damages. K-C's liability for breach of contract, tort or other cause of action shall not exceed the product purchase price. Purchasers and users are deemed to have accepted the above warranty and limitation of liability, and cannot change the terms by verbal agreement or by any writing not signed by K-C. To the extent required by applicable law, K-C does not limit its liability for death/injury resulting from K-C's negligence.

