



Nitrile

The world's leading disposable glove for chemical splash protection*

- Proprietary Ansell material formulation offers enhanced chemical splash protection
- Soft nitrile blend provides high levels of comfort
- Robust design for superior durability
- Highly versatile for use across a broad range of industries and applications
- Silicone free for product protection

Industries

- Automotive and transportation
- Chemical and petrochemical
- Food processing
- General industry
- Life sciences
- Machinery and equipment

Applications

- Chemical handling
- Cleaning equipment
- Industrial production
- Laboratory analysis
- Maintenance
- Meat, fish and food processing
- Sample taking and processing
- Transferring liquids and solids



TECHNICAL DATA SHEET:

PRODUCT INFORMATION:

Product	92-600	92-605
Material	Nitrile	
Color	Green	
Glove Design	Ambidextrous, Powder Free, Smooth Grip	Ambidextrous, Powder Free, Textured Fingers
Cuff	Beaded Cuff	
Manufacturing/ QMS Audit Standards	ISO 9001	
Regulatory/Standards Compliance	EN420, EN374/1,2,3, ASTM D6319, FDA 21 CFR 177-2600, Compliant with U.S. Food Contact Regulations, Arrete 09/11/04, European Regulation 1935/2004, German Recommendation for Food Commodities.	
Packaging	100 gloves per dispensers, 10 dispensers per shipper carton, 1000 gloves per shipper cartons	
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.	
Country of Origin	Sri Lanka / Thailand	Thailand
User Needs Segment	Robust Glove - Gloves that provide added strength, durability and chemical splash protection for longer wear times.	High Risk Glove - Extended cuff gloves that provide additional protection for the wrist and the forearm.

PHYSICAL PROPERTIES:

PROPERTY		TYPICAL VALUES				TESTING METHOD
SIZE		S 6½-7	M 7½-8	L 8½-9	XL 9½-10	ASTM D3767/EN 420
Length (mm/in)	92-600	240/9.5	240/9.5	240/9.5	240/9.5	
	92-605	300/11.8	300/11.8	300/11.8	300/11.8	
Average Palm Width (mm/in)	92-600	85/3.35	96/3.74	105/4.13	111/4.37	
	92-605	82/3.23	90/3.54	99/3.90	105/4.13	

Freedom from Holes (Inspection level I)	92-600	4.0 AQL (Americas) / 1.5 AQL (Outside of Americas)	ASTM D5151/EN 374-2
	92-605	All regions 1.5 AQL	
Palm Thickness Single Wall	mm: 0.12 / mils: 4.7		ASTM D3767/EN 420

BEFORE AGING		AFTER AGING		
Ultimate Tensile Strength	> 14 Mpa	> 14 Mpa		ASTM D 412-06a
Elongation at Break (%)	> 500	> 400		ASTM D 412-06a
Force at break (N)	> 6	> 6		EN 455-2

ORDERING INFORMATION:

	SIZE	S 6½-7	M 7½-8	L 8½-9	XL 9½-10
92-600	ASPN US	552822	552823	552824	552825
	ORACLE US	105077	105018	105079	105080
	ASPN OTHERS	552942	552943	552944	522945
92-600 VEN	CANADA MPRN	9260000S-VEN	9260000M-VEN	9260000L-VEN	926000XL-VEN
92-605	ASPN	588104	588105	588106	588107

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

*Warning: No glove provides complete protection against all chemicals. Users must test the gloves against the particular chemicals and environment in which they will be used.

Regulatory Compliance



Performance Standards

92-600



92-605



Distributed by:

NELSON JAMESON

800-826-8302 nelsonjameson.com

INC.

Ansell