

## TECHNICAL DATA SHEET:

### PRODUCT INFORMATION:

BLAZE®	
Material	Nitrile
Color	High Visibility Orange
Glove Design	Ambidextrous, Powder-Free, Chlorinated, Textured Fingers
Cuff	Beaded Cuff
Audit Standards	ISO 13485
Regulatory Compliance	US QSR/FDA 510(K), US NFPA
Packaging	100 gloves per dispenser, 10 dispensers per shipper carton, 1000 gloves per shipper carton.
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country of Origin	Malaysia

### PHYSICAL PROPERTIES:

	TYPICAL VALUES					TESTING METHOD
	6.5 - 7 S	7.5 - 8 M	8.5 - 9 L	9.5 - 10 XL	10.5 - 11 XL	
Length (mm)	270	270	270	270	270	ASTM D3767/EN 420
Average Palm Width (mm)	85	95	105	115	125	
Freedom from Holes (Inspection level I)	1.5 AQL					ASTM D5151/EN 374-2
Palm Thickness Single Wall	(mm : 0.13) / (mil : 5.1)					ASTM D3767/EN 420
	BEFORE AGING		AFTER AGING			
Ultimate Tensile Strength	33 Mpa		37 Mpa		ASTM D 412-06a	
Elongation at Break (%)	> 500		> 400		ASTM D 412-06a	
Force at break (N)	16		17		EN 455-2	

### ORDERING INFORMATION:

	SIZE	6.5 - 7 S	7.5 - 8 M	8.5 - 9 L	9.5 - 10 XL	10.5 - 11 XL
BLAZE®	REORDER NO.	N481	N482	N483	N484	N485

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application

Distributed by:  
  
 INC.  
 800-826-8302 nelsonjameson.com