

How to Order Sanitary Hose Assemblies

Build Your Assembly Part Number



PSD	200	SL	200 TC	200 TC	S	180 (inches)
Hose	ID Size	Fitting Style	Size First End Connection	Size Second End Connection	Hose Sleeve Stainless	Assembly Length

Rubber

PSD	Gray Protector	025 = 1/4"
PSDW	White Protector	037 = 3/8"
GRC	Red Gladiator	050 = 1/2"
SSW	Blue Sentry	062 = 5/8"
REB	Red ExtremeFlex Bev	075 = 3/4"
REBG	Gray ExtremeFlex Bev	100 = 1"
RSD	Gray Suction & Discharge	150 = 1-1/2"
RSDR	Red Suction & Discharge	200 = 2"
RSDB	Blue Suction & Discharge	250 = 2-1/2"
RES	LT Blue Premium S & D	300 = 3"
RCR	Orange Crush Resistant	400 = 4"
RBT	Purple Beverage	600 = 6"
RWS	Red Wine & Sprits	
RCT	White Comestible	
RWD	Premium Washdown	
TRS	Green EPDM/FEP Lined	
SW630	Food Suction	

PVC

CCT	Clear Tubing
CBT	Braided Tubing
CSS	Wire Helix

Silicone

SXW	Silicone Wire Reinforced
SXD	Silicone Multi Ply Discharge
SDB	Silicone Double Braid Discharge
SSD	Silicone Single Braid Discharge

Stainless Steel Overbraid PTFE

TSC	Silicone Covered PTFE Smooth Bore
TSB	SS Braided PTFE Smooth Bore
TCB	SS Braided PTFE Convuluted

End Connection

TC	Sanitary Clamp
BS	Bevel Seat with Hex Nut
BT	Bevel Male Thread
IF	Female I-Line
IM	Male I-Line
JP	John Perry with Hex Nut
JT	John Perry Male Thread
MT	Male Pipe Thread
TE	Tube End (Butt Weld)
DF	Cam & Groove Female
AM	Cam & Groove Male
AF	Flange
QL	Q-Line

Over all length tolerances for assemblies are:

- 1/4" on assemblies to 24"
- 1/2" on assemblies 25" to 60"
- 1% on assemblies over 60"

Build Your Custom Assembly in Just 7 Easy Steps.

- 1 Select code for hose style.
- 2 Specify hose ID.
- 3 Coupler style.
SL = radial crimp/permanent
- 4 & 5 Specify size and connection of each end fitting.
- 6 Hose sleeve material
S = Stainless Steel
- 7 Specify overall assembly length in inches.

Need help?

We can recommend the right hose for your application!
Call our hose specialists for assistance.